



4900-4990 MHz VERTICALLY POLARIZED SECTOR ANTENNA

The 90° vertically polarized sector antenna systems offered by Laird are designed specifically for public safety applications in the 4.9 GHz licensed band. The utilization of high gain sector antennas can provide better and more controlled wireless coverage than the traditional omnidirectional antenna. Overall coverage distance can be improved because of the more directional signal from these antennas as well as the higher gains available. The UV stable fiberglass radome construction gives long service life under the most demanding conditions. The sectors come with a stainless steel scissor bracket mounting system for ease of installation and alignment.


FEATURES

- Vertically polarized
- High gain in compact package: 16 dBi gain, 90° beamwidth
- Type N female integrated connector
- Extremely rugged for long service life in extreme environments
- Weatherproof


MARKETS

- Public safety base stations
- Point-to-multi-point systems
- Public safety broadband wireless
- Federal and local government

PARAMETER	SPECIFICATIONS
Frequency range	4900 - 4990 MHz
VSWR	1.5:1
Impedance	50 ohm
Input power	50 W
Pole diameter (OD)	1 - 2.4 in (25 - 60 mm)
Operating temperature	-40 to +70°C
Gain	16 dBi
Horizontal beamwidth	90°
Vertical beamwidth	9°
Mechanical downtilt	10°
Weight	5.7 lbs (2.6 kg)
Dimensions (L x W x H)	20 x 6 x 2.4 in (500 x 155 x 60 mm)



E Plane 4940 MHz



H Plane 4940 MHz

WIND LOADING

MODEL	SQ. IN	100 MPH	125 MPH	100 MPH 1/2 IN RADIAL ICE
SA49-90-16	120	30 lb	47 lb	32 lb

SYSTEM ORDERING

SA49-90-16 16 dBi 90° 4.9 GHz VPOL sector antenna

ANT-DS-SA49 1114

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2014 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com