

## APPLICATION

Home, Office, Internet Bar

## FEATURES

- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function
- USB/RS-232 communication port and RJ-11 protection

## PHASE (ONLY FOR ONLINE UPS)

**Phase:** 1-phase in / 1-phase out

## INPUT

**Capacity:** 2000 VA / 1200 W  
**Voltage:** 110/120 VAC or 220/230/240 VAC  
**Voltage Range:** 81-145 VAC / 162-290 VAC  
**Frequency Range:** 60/50 Hz (auto sensing)

## OUTPUT

**AC Voltage Regulation (Batt. Mode):** ±10%  
**Frequency Range (Batt. Mode):** 60 Hz or 50 Hz ±1 Hz  
**Transfer Time:** Typical 2 ~ 6 ms,  
**Waveform (Batt. Mode):** Simulated Sine Wave

## BATTERY

**Battery Type:** 12 V/9 Ah  
**Battery Number:** 2  
**Typical Recharge Time:** 4-6 hours up to 90% capacity



## SAFETY STANDARD APPROVAL



## PROTECTION

**Full Protection:** Overload, Discharge, and Overcharge Protection

## PHYSICAL

**Output Receptacles:** India, French, Schuko, NEMA, and IEC ions  
**Dimension:** 397mm(L) x 146mm(W) x 205mm(H)  
**Net Weight (kgs):** 11.5

## OPERATING ENVIRONMENT

**Humidity:** 0-90 % RH @ 0- 40°C (non-condensing)  
**Noise Level:** Less than 40dB

## MANAGEMENT

**Optional USB/RS-232 Port:** Support Windows 98/2000/2003/XP/Vista/2008, Windows 7, Linux, and MAC8

This content is subject to change, please refer to specification for more detail.  
 FSP reserve the right to change the content without prior notice