

SMA Female Connector Solder Attachment for RG58, RG55, RG142, RG223, RG400



# **RF Connectors Technical Data Sheet**

### Confguration

- SMA Female Connector
- MIL-STD-348A
- 50 Ohms

#### Features

Gold Plated Beryllium Copper Contact

### Applications

- General Purpose Test
- Custom Cable Assemblies

#### Description

Pasternack's PE4041 SMA female connector with solder/solder attachment for RG58, RG55, RG142, RG223 and RG400 is part of our full line of RF components available for same-day shipping.

Our SMA female connector PE4041 datasheet specifcations an Pasternack's broad catalog of RF, microwave and millimeter their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly confguration, Pasternack has the right conn cable assemblies for you and ship same-day.

#### Mechanical Specifcations

Size	
Length	0.91 in [23.11 mm]
Width/Dia.	0.25 in [6.35 mm]
Weight	0.006 lbs [2.72 g]

Material Specifcations

Description	Material	Plating
Contact	Beryllium Copper	Gold 50 µin minimum
Insulation	PTFE	
Body	Brass	Nickel 100 µin minimum
Crimp Sleeve	Brass	Gold

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, i n v e n t o r y a n dSM& Fermatlei Concreatori SoldreisAttachment for RG58, RG55, RG142, RG223, RG400 PE4041

## **PE4041**

- Straight Body Geometry
- RG58, RG55, RG142, RG223, RG400 Interface Type
- Solder/Solder Attachment

• 50 µin minimum contact plating

P E 4 O 4C1A D D r a wi n g SMA Female Connector Solder Attachment for RG58, RG55, RG142, RG223, RG400

