






1. Mechanical Dimensions:



2. Schematic:



3. Electrical Specifications: @25°C

OCL: 250nH±10% @100KHz 0.1V,

Q : tbd Min @100KHz 0.1V

DCR: 0.3 mOhms ±20%

Isat: 70.0Adc (Based on 20% Drop Typ)

Irms: 75.0A (Based on 40°C Typ Temp Rise)

SRF : tbd Min

Notes:

1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. All listed parameters are to be within tolerance from -40°C to +125°C unless otherwise noted.
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component
11. Outsourced item processed & controlled under XFMRs QA system

PRELIMINARY

DOC REV: A/-

XFMRs Inc www.XFMRs.com	Title: SURFACE MOUNT HIGH CURRENT INDUCTOR		
	UNLESS OTHERWISE SPECIFIED		P/N: XFHCL0810F-R25K
TOLERANCES: xx ±0.50 Dimensions in MM	DWN.	Xiang	Oct-15-15
	CHK.	YK Liao	Oct-15-15
SHEET 1 OF 1	APP.	BW	Oct-15-15

PROPRIETARY

Document is the property of XFMRs Group & is not allowed to be duplicated without authorization.