

SHINDENGEN

Schottky Rectifiers (SBD)

Dual


SF20JC6

60V 20A

OUTLINE DIMENSIONS

Case : FTO-220

Unit : mm



RATINGS


● Absolute Maximum Ratings (Unless otherwise specified, Tc=25°C)

Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-55~150	°C
Operating Junction Temperature	Tj		150	°C
Maximum Reverse Voltage	V _{RM}		60	V
Repetitive Peak Surge Reverse Voltage	V _{RRSM}	Pulse width 0.5ms, duty 1/40	65	V
Average Rectified Forward Current	I _o	50Hz sine wave, R-load, Rating for each diode I _o /2, T _c =115°C	20	A
Peak Surge Forward Current	I _{FSM}	50Hz sine wave, Non-repetitive 1 cycle peak value, T _j =25°C	200	A
Dielectric Strength	V _{dis}	Terminals to case, AC 1 minute	2	kV
Mounting Torque	T _{OR}	(Recommended torque: 0.3N·m)	0.5	N·m


● Electrical Characteristics (Unless otherwise specified, Tc=25°C)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V _F	I _F =10A, Pulse measurement, Rating of per diode	Max 0.69	V
Reverse Current	I _R	V _R =V _{RM} , Pulse measurement, Rating of per diode	Max 0.7	mA
Junction Capacitance	C _j	f=1MHz, V _R =10V, Rating of per diode	Typ 335	pF
Thermal Resistance	θ _{jc}	junction to case	Max 2.0	°C/W



SF20JC6 Forward Voltage



SF20JC6 Reverse Current




SF20JC6 Forward Power Dissipation




SF20JC6

Reverse Power Dissipation




$T_j = 150^\circ\text{C}$




SF20JC6


Derating Curve



$V_R = 30V$



SF20JC6 Peak Surge Forward Capability



SF20JC6 Junction Capacitance

