


isc N-Channel MOSFET Transistor

FDP053N08B
• FEATURES

- With TO-220 packaging
- High speed switching
- Very high commutation ruggedness
- Easy to use
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operationz

• APPLICATIONS


- PFC stages
- LCD & PDP TV
- Power supply
- Switching applications


• ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage	80	V
V_{GSS}	Gate-Source Voltage	± 20	V
I_D	Drain Current-Continuous@ $T_c=25^\circ\text{C}$ $T_c=100^\circ\text{C}$	120 82.5	A
I_{DM}	Drain Current-Single Pulsed	480	A
P_D	Total Dissipation	146	W
T_j	Operating Junction Temperature	-55~175	°C
T_{stg}	Storage Temperature	-55~175	°C

• THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th(ch-c)}$	Channel-to-case thermal resistance	1.03	°C/W
$R_{th(ch-a)}$	Channel-to-ambient thermal resistance	62.5	°C/W



isc N-Channel MOSFET Transistor

FDP053N08B

ELECTRICAL CHARACTERISTICS

 $T_c=25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-Source Breakdown Voltage	$\text{V}_{\text{GS}}=0\text{V}; \text{I}_D= 0.25\text{mA}$	80			V
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	$\text{V}_{\text{DS}}=10\text{V}; \text{I}_D=0.25\text{mA}$	2.5		4.5	V
$\text{R}_{\text{DS(on)}}$	Drain-Source On-Resistance	$\text{V}_{\text{GS}}= 10\text{V}; \text{I}_D=75\text{A}$		4.2	5.3	$\text{m}\Omega$
I_{GSS}	Gate-Source Leakage Current	$\text{V}_{\text{GS}}= \pm 20\text{V}; \text{V}_{\text{DS}}= 0\text{V}$			± 0.1	μA
I_{DSS}	Drain-Source Leakage Current	$\text{V}_{\text{DS}}= 64\text{V}; \text{V}_{\text{GS}}= 0\text{V}; \text{T}_j=25^\circ\text{C}$ $\text{V}_{\text{DS}}= 64\text{V}; \text{V}_{\text{GS}}= 0\text{V}; \text{T}_j=125^\circ\text{C}$			1 500	mA
V_{SDF}	Diode forward voltage	$\text{I}_{\text{SD}}=75\text{A}, \text{V}_{\text{GS}} = 0 \text{ V}$			1.3	V