

ELV90-24-3R8



<b>Sales Region</b>	Worldwide
<b>Series</b>	ELV
<b>Status</b>	Production
<b>Feature</b>	for LED drive
<b>Option</b>	
<b>Option Lineup</b>	
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



Electrical Characteristics	
Input Voltage Range[AC]	90 to 305V
Input Voltage Range[DC]	
Efficiency	88% Typ.
Rated Output Voltage[DC]	24V
Output Voltage Range[DC]	Fixed
Maximum Output Current	3.8A
Maximum Output Power	91.2W

Cases Shape & Size	
Case'□ shape	Unit
Width(W)	45.5mm Nom.
Height(H)	40.2mm Nom.
Depth(D)	228mm Nom.
Weight	830g Typ.

Other	
Operating Temp. Range	-25 to 50°C
Cooling	Convection cooling
Safety Standard(Certified)	CSA C22.2 No.250.13
	Den-an (Appendix 8, Appendix 10)
	EN61347-1
	EN61347-2-13
Safety Standard(Conformed)	UL8750
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.