

Components of electronic housing - UM-PRO PCB C-LOCK L2 BK - 2200165

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Locking element for locking the PCB onto UM-PRO housing at level 2

The figure shows the versions for PCB level 1

Why buy this product

- Available in individual lengths
- Available in the overall widths of 72 mm, 108 mm, and 122 mm
- ✓ Variety of connection technologies



Key Commercial Data

Packing unit	50 pc
GTIN	4 046356 547598
GTIN	4046356547598

Technical data

General

Housing type	Panel mounting base
Housing material	Polyamide
Color (RAL)	black

Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
---------------------------------	--

Standards and Regulations

Flammability rating according to UL 94	V0



Components of electronic housing - UM-PRO PCB C-LOCK L2 BK - 2200165

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approval details

UL Recognized



http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm

FILE E 240868

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com