



9.6×9.6 Square/ Single Turn /Trimming Potentiometer


-- 3386P--



... Install dimension.....



... Mutual dimension.....



Electrical Characteristics

- Standard Resistance Range.....50Ω~2MΩ
- Resistance Tolerance.....±10%
- Absolute Minimum Resistance.....≤1%R或10Ω
- Contact Resistance Variation.....CRV≤3%
- Insulation Resistance.....R1≥1GΩ (100Vac)
- Withstand Voltage.....600Vac
- Effective Travel.....300°

Environmental Characteristics


- Power Rating, 315 volts max
.....0.5W@70°C,0W@125°C
- Temperature Range.....-55°C~125°C
- Temperature Coefficient.....±250ppm/°C
- Temperature Variation.....-55°C,30min,+125°C

Standard Resistance Table

Resistance (Ohms)	Resistance Code
10	100
20	200
50	500
100	101
200	201
500	501
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
25,000	253
50,000	503
100,000	104
200,000	204
250,000	254
500,000	504
1,000,000	105
2,000,000	205

-30min 5cycles
-ΔR≤5%R,Δ(Uab/Uac)≤10%
- Collision.....100m/s²,1000cycles,ΔR≤2%R
- Electrical Endurance at 70°C.....0.5W@70°C
-1000h,ΔR≤10%R
-Δ(Uab/Uac)≤10%,CRV≤3% or 5Ω
- Rotational Life.....200cycles
-ΔR≤10%R,CRV≤3% or 5Ω

Physical Characteristics



Special resistances available