


SCHOTTKY BARRIER RECTIFIERS	REVERSE VOLTAGE - 20 to 100 Volts FORWARD CURRENT - 2.0 Amperes
------------------------------------	--

FEATURES

- Metal-Semiconductor junction with guard ring
- Epitaxial construction
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

MECHANICAL DATA

- Case: JEDEC DO-15 molded plastic
- Polarity: Color band denotes cathode
- Weight: 0.0125ounces , 0.4 grams
- Mounting position: Any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave ,60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	SR220	SR230	SR240	SR250	SR260	SR280	SR2100	UNIT	
Maximum Recurrent Peak Reverse Voltage	VRRM	20	30	40	50	60	80	100	V	
Maximum RMS Voltage	VRMS	14	21	28	35	42	56	70	V	
Maximum DC Blocking Voltage	VDC	20	30	40	50	60	80	100	V	
Maximum Average Forward Rectified Current @TA =75 °C	I(AV)	2.0							A	
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load(JEDEC Method)	IFSM	60							A	
Maximum Forward Voltage at 2.0A DC	VF	0.45	0.55	0.6	0.7		0.85		V	
Maximum DC Reverse Current @TJ=25°C at Rated DC Blocking Voltage @TJ=100°C	IR	1.0				100				mA
Typical Junction Capacitance (Note1)	CJ	150							pF	
Typical Thermal Resistance (Note2)	RθJA	20							°C/W	
Operating Temperature Range	TJ	-55 to +150							°C	
Storage Temperature Range	TSTG	-55 to +150							°C	

NOTES: 1.Measured at 1.0 MHz and applied reverse voltage of 4.0V DC
 2.Thermal resistance junction to ambient,

RATING AND CHARACTERISTIC CURVES

SR220 thru SR2100



FIG. 1 – FORWARD CURRENT DERATING CURVE




FIG. 2 – MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 – TYPICAL JUNCTION CAPACITANCE




FIG.4-TYPICAL FORWARD CHARACTERISTICS




FIG.2-TYPICAL REVER CHARACTERISTICS

