# FEATURES AND SPECIFICATIONS



### The new Quad LC Adapter from Molex provides multiple connection options from a single adapter

Designed for high-density applications, the quad LC adapter from Molex provides a 4-position LC adapter solution. Four LC ports are provided in 1 adapter, allowing for multiple LC connectors to be mated within the adapter. Connection options include 4 simplex LC connectors, 2 simplex and 1 duplex LC connectors or 2 duplex LC connectors.

The quad LC adapter is available in either a snapmount or screw-mount installation style. Individual shutters on one side of the adapter are available as an eye-safety option, providing protection even when the adapter is not fully populated. The adapter is available with either Phosphor Bronze or Zirconia Ceramic alignment sleeves to accommodate either singlemode, multimode or Angle Polish (APC) connectors. Mounting dimensions of the quad LC adapter are identical to the duplex SC adapter and can be used as direct a drop-in replacement.

The quad LC adapter from Molex is the newest addition to this robust small form-factor product family. Products include simplex and duplex connectors, adapters and cable assemblies. For more detailed information, please visit: www.molex.com/fiber/ lc.html.

#### **Features and Benefits**


- Four LC ports provide multiple simplex or duplex connection options
- Ceramic or Phosphor Bronze alignment sleeves accommodate singlemode and multimode operation
- Safety shutters available to prevent eye injury when a connector is not installed

# **SPECIFICATIONS**

# **Reference Information**

Packaging: Individual bag Mates With: Simplex or duplex LC connectors (Series 86024, 86025) Designed In: Millimeters

*Mechanical* Durability: 200 cycles min.



- Snap or screw-style mounting allows for installation flexibility
- SC duplex compatible mounting provides a direct drop-in replacement solution for density upgrade

Physical Housing: Polymer Alignment sleeve: Zirconia Ceramic or Phosphor Bronze Operating Temperature: -40 to +85°C

# Telecommunications

- Hubs
- Servers
- Routers
- Other Markets
  - Optical DVI
  - Storage servers
  - Local Area Networks (LANs)
  - Premise distribution





# **ORDERING INFORMATION**

Order No.	Mode	Alignment Sleeve	Mounting Style	Housing Color	Shutters
106123-0200	Singlemode	Zirconia Ceramic	Screw	Blue	Yes
106123-1200	Multimode	Phosphor Bronze	Screw	Beige	Yes
106123-2200	Singlemode	Zirconia Ceramic	Screw	Green	Yes
106123-3200	Multimode	Phosphor Bronze	Screw	Aqua	Yes
106123-0400	Singlemode	Zirconia Ceramic	Snap	Blue	Yes
106123-1400	Multimode	Phosphor Bronze	Snap	Beige	Yes
106123-2400	Singlemode	Zirconia Ceramic	Snap	Green	Yes
106123-3400	Multimode	Phosphor Bronze	Snap	Aqua	Yes
106123-0100	Singlemode	Zirconia Ceramic	Screw	Blue	No
106123-1100	Multimode	Phosphor Bronze	Screw	Beige	No
106123-2100	Singlemode	Zirconia Ceramic	Screw	Green	No
106123-3100	Multimode	Phosphor Bronze	Screw	Aqua	No
106123-0300	Singlemode	Zirconia Ceramic	Snap	Blue	No
106123-1300	Multimode	Phosphor Bronze	Snap	Beige	No
106123-2300	Singlemode	Zirconia Ceramic	Snap	Green	No
106123-3300	Multimode	Phosphor Bronze	Snap	Aqua	No

Americas Headquarters Lisle, Illinois 60532 U.S.A. 1-800-78M0LEX amerinfo@molex.com

Far East North Headquarters Yamato, Kanagawa, Japan 81-462-65-2324 feninfo@molex.com

rs Far East South Headquarters Europe Jurong, Singapore Munich, 65-6-268-6868 49-89-4 fesinfo@molex.com eurinfoc Visit our website at www.molex.com/product/fiber/quadlc.html

European Headquarters Munich, Germany 49-89-413092-0 eurinfo@molex.com Corporate Headquarters 2222 Wellington (t. Lisle, IL 60532 U.S.A. 630-969-4550 Fax:630-969-1352

Order No. USA-335 Rev. 1

Printed in USA/JI/2006.03