



NOTES:

1. MATERIAL: NYLON 6/6 (RMS-01), COLOR NATURAL.
2. FLAME RETARDANT NYLON (RMS-19). COLOR NATURAL. AVAILABLE BY SPECIAL ORDER ONLY; TO ORDER USE P/N FTH-13R-19 OR FTH-13S-19.
3. UV STABILIZED NYLON 6/6 (RMS-46), COLOR BLACK. AVAILABLE BY SPECIAL ORDER ONLY; TO ORDER USE P/N FTH-13R-UVB OR FTH-13S-UVB.
4. MOUNTING SCREW FOR FTH-13R: NO. 8 (M4) PAN HEAD, MOUNTING SCREW FOR FTH-13S: NO. 8 (M4) FLAT HEAD OR NO. 6 (M3.5) FLAT, ROUND, OR PAN HEAD.

MOUNTING RIVETS FOR - FTH-13R		
USE RIVET NO.	HOLE DIA.	FOR PANEL THICKNESS RANGE
SR-4050	.161 (4.1)	.018-.058 (0.5-1.5)
SR-4060		.058-.097 (1.5-2.5)
SR-4070		.097-.137 (2.5-3.5)
SR-4080		.137-.176 (3.5-4.5)
SR-4100		.215-.255 (5.5-6.5)

TITLE: FLAT TIE HOLDER			DWG IN IN (MM) FINAL			
D SEE ECN #1124 FOR CHANGES SK 01.24.06		TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC=±1/64 ANG=±1°		FILE # FTH-13X DWN: E.P. APP:		PART # FTH-13 SERIES PRINT TYPE CA
C UPDATED PRINT AND CHANGED FILE NO. SM 05.20.02		MAT'L: SEE NOTES		DT: 12-30-98 DT:		
B REDRAWN TO INCLUDE FTH-13S-01 DWG. RG11/02/00		RE: RICHCO, INC.		RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060		
A FR NYLON 66 (RMS-19) ADDED JL 01.06.00						
REV DESCRIPTION ENGR DATE						