

## **VCO Product Specification**

 Model:
 VCO190-1455T(Y)
 Rev:
 Date: 8/30/2006

 Customer:
 SIRENZA MICRODEVICES, INC.

**Operating Temperature Range:** (-35 ° to 85 ° C)

## **Pb** RoHS Compliant

To order models as RoHS Compliant add "Y" suffix to base model number.

Parameter	Min	Тур	Max	Units	X	Remarks
Frequency Range -	1445	1455	1465	MHz	Х	
Tuning Voltage:						
1445 MHz	0.5	1		Vdc	Х	
1465 MHz		4	4.5	Vdc	Х	
Tuning Sensitivity -	10	15	20	MHz/V	Х	
Output Power -	-2	1	4	dBm	Х	
Output Phase Noise:						
10 kHz		-109	-103	dBc/Hz		
100 kHz		-130	-124	dBc/Hz	Х	
Power Supply -	4.75	5	5.25	Volts		
Supply Current -		25	30	mA	Х	
larmonic Suppression:						
2nd Harmonic		-15	-10	dBc	Х	
3rd Harmonic		-20	-15	dBc	Х	
Spurious (Non-Harmonic) -			-90	dBc		
requency Pushing - 4.75-5.25 V		0.5	1	MHz p-p		
Frequency Pulling - 12 dB RL		0.5	1	MHz p-p		
Funing Port Capacitance -		47		pF		
Output Impedance -		50		Ω		

## Package Information

Package Type: T (0.5 x 0.5 x 0.156 inches)	Drawing Number:	60035
--	-----------------	-------

## Comments

 $\boldsymbol{X}$  Indicates parameter to be tested 100% in production

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices and/or systems.

Page 1 of 1

Sirenza Microdevices, Inc.

fax 303.410.7988

tel 303.327.3030 fax 303.4