


Making Light Work For You!

<p>Industrial Panel Indicator</p>  <p style="font-size: small;">Dimensions in mm (typical) Not to Scale</p> <p style="font-size: small;">Anode Indicated by Red Sleeve</p>	<p style="text-align: right;">Ø 12.7mm Mounting</p> <ul style="list-style-type: none"> • Nickel Plated Brass Body Finish • Five High Intensity Colours • Flying Lead Terminations available • Voltage range up to 230Vac • Panel Sealing in excess of IP66 • Robust termination tags accept push-on connectors
--	---

512 SERIES

Mean Time Between Failure 100,000 Hours

Operating Temperature Range: -20 to +60°C

Storage Temperature Range: -30 to +85°C

Order Code : 512 – 501 – 21

<p>Series Options :</p> <p>511 – Coloured Diffused Lens</p> <p>512 – Smoked Lens</p>	<p>LED Options : Code – LED Colour / Intensity @ 20 mA</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>501 – Red 660nm</td> <td style="text-align: right;">2750 mcd</td> </tr> <tr> <td>521 – Yellow 590nm</td> <td style="text-align: right;">4800 mcd</td> </tr> <tr> <td>532 – Green 525nm</td> <td style="text-align: right;">6000 mcd</td> </tr> <tr> <td>930 – Blue 470nm</td> <td style="text-align: right;">2000 mcd</td> </tr> <tr> <td>997 – White *</td> <td style="text-align: right;">4000 mcd</td> </tr> </table> <p style="font-size: x-small;">Intensity figures are typical and apply to discrete LED (non flat-topped) Package power dissipation (max)</p>	501 – Red 660nm	2750 mcd	521 – Yellow 590nm	4800 mcd	532 – Green 525nm	6000 mcd	930 – Blue 470nm	2000 mcd	997 – White *	4000 mcd	<p>Voltage Options : Code – Voltage / Current</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>21 – 12Vdc @ 20mA</td> </tr> <tr> <td>22 – 24Vdc @ 20mA</td> </tr> <tr> <td>23 – 28Vdc @ 20mA</td> </tr> <tr> <td>24 – 48Vdc @ 20mA</td> </tr> <tr> <td>75 – 110Vac @ 9mA *</td> </tr> <tr> <td>76 – 230Vac @ 4mA *</td> </tr> </table> <p>* Insulated Connectors must be used at these voltages.</p>	21 – 12Vdc @ 20mA	22 – 24Vdc @ 20mA	23 – 28Vdc @ 20mA	24 – 48Vdc @ 20mA	75 – 110Vac @ 9mA *	76 – 230Vac @ 4mA *
501 – Red 660nm	2750 mcd																	
521 – Yellow 590nm	4800 mcd																	
532 – Green 525nm	6000 mcd																	
930 – Blue 470nm	2000 mcd																	
997 – White *	4000 mcd																	
21 – 12Vdc @ 20mA																		
22 – 24Vdc @ 20mA																		
23 – 28Vdc @ 20mA																		
24 – 48Vdc @ 20mA																		
75 – 110Vac @ 9mA *																		
76 – 230Vac @ 4mA *																		

Materials :

Body and Nut: Bright Nickel Plated Brass
 Lens: Polycarbonate
 Termination: Silver Plated Brass 2.8mm Flat Tags
 Panel Seal: Fluoroelastomer
 Lockwasher: Zinc Plated Steel

Technical Information :

Panel Cutout: 12.7mm
 Min. Mounting Centres: x,y = 19.5mm
 Min/Max Panel Thickness: 1.5-8.0mm
 Mounting Torque: 1.0Nm
 Max. Reverse Voltage: 1000Vdc
 IP Rating: 66

* Typical emission colour: x=0.31, y=0.32
 Colour temperature 8000K
 Intensities (Iv) and colour shades of white (x, y co-ordinates) may vary between LEDs within a batch

Marl International Limited Ulverston, Cumbria. LA12 7RY England

Tel : + 44 (0) 1229 582430 Fax : + 44 (0) 1229 585155

E-mail : sales@marl.co.uk Website : www.marl.co.uk

The company's services are recognised to the Internationally recognised quality standard BS EN ISO9001 : 1994

The information above does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. No responsibility can be assumed for inaccuracies or printing errors. Marl International Ltd. reserve the right to alter without notice the specification or any condition of supply for products or service.