

SPECIFICATION SHEET

JFW MODEL 50R-310

ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-2700 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-10 dB in 1 dB steps
VSWR	1.2:1 maximum DC-1000 MHz 1.3:1 maximum 1000-2700 MHz
Insertion Loss	0.4 dB maximum 0.11 dB typical @ 1000 MHz 0.23 dB typical @ 2700 MHz
Attenuation Accuracy	± 0.4 dB DC-1000 MHz ± 0.5 dB 1000-2700 MHz
RF Input Power	2 Watts average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	SMA female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-039

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	06/13/2001			16357	09/30/2008	C	TRS 09/30/2008
9999	05/05/2003	A	BAC 09/08/2005	16402	10/15/2008	D	TRS 10/15/2008
11844	09/07/2005	B	BAC 09/08/2005	16574	12/02/2008	E	TRS 12/02/2008