

**SPECIFICATION SHEET**  
**JFW MODEL 50P-034**  
**RELAY PROGRAMMABLE ATTENUATOR**

JFW Industries, Inc.  
 Phone: 317-887-1340  
 sales@jfwindustries.com  
 www.jfwindustries.com

Frequency Range	DC-1500 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-100 dB in 10 dB steps
Attenuation Steps	10, 20, 30 and 40 dB
VSWR	1.4:1 maximum DC-1000 MHz 1.5:1 maximum 1000-1500 MHz
Attenuation Accuracy	± 0.5 dB DC-500 MHz ± 1.0 dB 500-1000 MHz ± 1.5 dB 1000-1500 MHz
Insertion Loss	2 dB maximum
RF Input Power	1 Watt average
Peak Power	1000 Watts (1 usec pulse)
Switching Speed	6 milliseconds
Control	+12 Vdc @ 30 mA per relay
DC Connector	Solder terminals
RF Connector	BNC, SMA, N or TNC female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-745

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	04/12/2004	A	BAC 06/21/2007				