

T-79-07-10

**élantec**  
HIGH PERFORMANCE ANALOG INTEGRATED CIRCUITS

**EHA2500 Series**  
High Slew Rate Operational Amplifier

EHA2500

**Features**

- High slew rate—100 V/μs
- Fast settling—200 ns
- Wide power bandwidth
- High input impedance
- Low offset current—25 nA
- Compensated versions available

**Applications**

- Data acquisition systems
- R.F. amplifiers
- Video amplifiers
- Signal generators
- Pulse amplification
- High speed sample and holds

**General Description**


Elantec's EHA2500 Series of monolithic high slew rate amplifiers is designed and optimized for high slew rates and wide bandwidths. Three different types are offered. The EHA250X series is unity gain stable and low cost. The EHA251X series has twice the bandwidth and slew rate of the EHA250X series and is also unity gain stable. For the best AC performance choose the EHA252X series which has the highest slew rate—120 V/μs—and the widest bandwidths available. The EHA252X series is stable with closed loop gains as low as three.

These devices are fabricated using Elantec's Dynamic Dielectrically Isolated process that has excellent PNPs and NPNs that allow higher bandwidths than standard junction isolated process.


Elantec's high speed amplifiers are widely used in military, video and medical applications. They are especially suited for high speed video amplifiers, pulse detectors, and wide bandwidth filters.

Elantec's facilities comply with MIL-I-45208A and other applicable quality specifications. For information on Elantec's military processing, request our brochure: *Elantec's Military Processing—Monolithic Products.*


**Connection Diagrams**




EHA3-, EHA7-



EHA4-



EHA2-



EHA9-

TOP VIEWS

JANUARY 1988 REV D

# EHA2500 Series

## High Slew Rate Operational Amplifier

### Selection Guide

Part Number	Temp.	V <sub>OS</sub> (Max) mV	I <sub>BIAS</sub> (Max) nA	I <sub>OS</sub> (Max) nA	G <sub>BW</sub> (Typ) MHz	PBW (Min) kHz	S <sub>R</sub> (Min) V/μs	t <sub>SET</sub> (Typ) μs	PSRR, CMRR (Min) dB	R <sub>IN</sub> (Min) MΩ	Minimum Stable Gain
EHA2500	M	5	200	25	12	350	25	0.33	80	25	1
EHA2502	M	8	250	50	12	300	20	0.33	74	20	1
EHA2505	C	8	250	50	12	300	20	0.33	74	20	1
EHA2510	M	8	200	25	12	750	50	0.25	80	50	1
EHA2512	M	10	250	50	12	600	40	0.25	74	40	1
EHA2515	C	10	250	50	12	600	40	0.25	74	40	1
EHA2520	M	8	200	25	20	1500	100	0.20	80	50	3
EHA2522	M	10	250	50	20	1200	80	0.20	74	40	3
EHA2525	C	10	250	50	20	1200	80	0.20	74	40	3

### Ordering Information

Dice (Note 1) (EHA0-)	14-Pin DIP Ceramic (EHA1-)	TO-99 Metal Can (EHA2-)	8-Pin DIP Plastic (EHA3-)	LCC 20-Pin (EHA4-)	8-Pin DIP Cerdip (EHA7-)	10-Pin Flat-Pack (EHA9-)
EHA0-2500-6		EHA2-2500/883B EHA2-2500-2		EHA4-2500/883B	EHA7-2500/883B EHA7-2500-2	EHA9-2500/883B
EHA0-2502-6		EHA2-2502/883B EHA2-2502-2		EHA4-2502/883B	EHA7-2502/883B EHA7-2502-2	EHA9-2502/883B
EHA0-2505-6		EHA2-2505-5	EHA3-2505-5		EHA7-2505-5	
EHA0-2510-6		EHA2-2510/883B EHA2-2510-2		EHA4-2510/883B	EHA7-2510/883B EHA7-2510-2	EHA9-2510/883B
EHA0-2512-6		EHA2-2512/883B EHA2-2512-2		EHA4-2512/883B	EHA7-2512/883B EHA7-2512-2	EHA9-2512/883B
EHA0-2515-6		EHA2-2515-5	EHA3-2515-5		EHA7-2515-5	
EHA0-2520-6	Consult Factory	EHA2-2520/883B EHA2-2520-2		EHA4-2520/883B	EHA7-2520/883B EHA7-2520-2	EHA9-2520/883B
EHA0-2522-6		EHA2-2522/883B EHA2-2522-2		EHA4-2522/883B	EHA7-2522/883B EHA7-2522-2	EHA9-2522/883B
EHA0-2525-6		EHA2-2525-5	EHA3-2525-5		EHA7-2525-5	

Note 1: Dice are available in waffle packs. Consult factory for more information.  
 Note 2: Consult factory for special packaging or temperature range requirements.

PREFIX	SUFFIX
P	-1 0°C to 200°C
EHA2- TO-99 Metal Can . . . . .	-2 -55°C to 125°C
EHA3- 8-Pin Plastic DIP . . . . .	-3
EHA4- Leadless Chip Carrier (LCC) . . . . .	-4 -25°C to 85°C
EHA7- 8-Pin CERDIP . . . . .	-5 0°C to 75°C
EHA9- Flat-Pack . . . . .	-6 100% 25°C Probe (Dice Only)
EHA0- Dice	-7
	/883B See Elantec's "Military Processing—Monolithic Products".
	-9


# EHA2500 Series

## High Slew Rate Operational Amplifier


### Test Level Descriptions

Test Level	Test Procedure
I	100% production tested and QA sample tested per QA test plan QCX0002.
II	100% production tested at $T_A = -25^\circ\text{C}$ , and QA sample tested at $T_A = -25^\circ\text{C}$ , $T_{MAX}$ and $T_{MIN}$ per QA test plan QCX0002.
III	QA sample tested per QA test plan QCX0002.
IV	Parameter is guaranteed (but not tested) by Design and Characterization Data.
V	Parameter is typical value for information purposes only.

### AC Test Circuits




EHA250X AND EHA251X




EHA252X

### Burn-In Circuit



### Die Layout



# EHA2500/2502/2505

## High Slew Rate Operational Amplifier

### Absolute Maximum Ratings

$V_S$	Supply Voltage	±20V	$T_A$	Operating Temperature Range:	
$V_{IN}$	Differential Input Voltage	±15.0V		EHA2500/02	-55°C to +125°C
$P_D$	Maximum Power Dissipation	See Curves		EHA2505	0°C to +75°C
$I_{OUT}$	Peak Output Current	50mA	$T_{ST}$	Storage Temperature Lead Temperature (soldering, 5 seconds)	-65°C to +150°C 300°C

**Important Note:** All parameters having Min./Max. specifications are guaranteed. The Test Level column indicates the specific device testing actually performed during production and Quality Assurance inspection. Elantec performs most electrical tests using modern high-speed automatic test equipment, specifically the LIX 77 Series system. Unless otherwise noted, all tests are pulsed tests, therefore  $T_J = T_C = T_A$ .

### DC Electrical Characteristics

$V_S = \pm 15V, R_S = 50\Omega, R_L = 100k\Omega, V_{CM} = 0V, V_{OUT} = 0V, T_{MIN} \leq T_A \leq T_{MAX}$ , unless otherwise specified.

Parameter	Test Conditions	EHA2500			EHA2502			EHA2505			Units			
		Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	Test Level	Min.		Typ.	Max.	Test Level
$V_{OS}$ Offset Voltage	$T_A = 25^\circ C$		2	5	I		4	8	I		4	8	I	mV
				8	I			10	I			10	III	mV
$\Delta V_{OS}/\Delta T$ Offset Voltage Drift			20		V		20		V		20		V	$\mu V/^\circ C$
$I_B$ Bias Current (Note 1)	$T_A = 25^\circ C$		100	200	I		125	250	I		125	250	I	nA
				400	I			500	I			500	III	nA
$I_{OS}$ Offset Current	$T_A = 25^\circ C$		10	25	I		20	50	I		20	50	I	nA
				50	I			100	I			100	III	nA
$R_{IN}$ Input Resistance	$T_A = 25^\circ C$		25	50	IV		20	50	IV		20	50	IV	M $\Omega$
$V_{CMR}$ Common-Mode Range			±10.0		I		±10.0		I		±10.0		II	V
$CMRR$ Common-Mode Rejection Ratio (Note 2)	$\Delta V_{CM} = \pm 10V$		80	90	I		74	90	I		74	90	II	dB
$PSRR$ Power Supply Rejection Ratio (Note 3)	$\Delta V_S = \pm 5V$		80	90	I		74	90	I		74	90	II	dB
$A_{VOL}$ Large Signal Voltage Gain (Note 4)	$R_L = 2k\Omega, V_{OUT} = \pm 10V, T_A = 25^\circ C$		20	30	I		15	25	I		15	25	I	V/mV
	$R_L = 2k\Omega, V_{OUT} = \pm 10V$		15		I		10		I		10		III	V/mV
$V_{OUT}$ Output Voltage Swing	$R_L = 2k\Omega$		±10.0	±12.0	I		±10.0	±12.0	I		±10.0	±12.0	II	V
$I_{OUT}$ Output Current	$V_{OUT} = \pm 10V, T_A = 25^\circ C$		±10	±20	I		±10	±20	I		±10	±20	I	mA
	$V_{OUT} = \pm 10V$		±7.5		I		±7.5		I		±7.5		III	mA
$I_{CC}$ Supply Current (Note 5)	$T_A = 25^\circ C$		4	6	I		4	6	I		4	6	I	mA
				6.5	I			7	I			7	III	mA

# EHA2500/2502/2505

## High Slew Rate Operational Amplifier

EHA2500/EHA2502/EHA2505

### AC Electrical Characteristics

$V_S = \pm 15V, A_V = 1, R_S = 50\Omega, R_L = 2k\Omega, C_L = 50pF, V_{OUT} = \pm 200mV, T_{MIN} < T_A < T_{MAX}$ , unless otherwise specified (See AC test circuit)

Parameter	Test Conditions	EHA2500			EHA2502			EHA2505			Units		
		Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	Test Level	Min.		Typ.	Max.
$t_r, t_f$ Rise and Fall Times	$T_A = 25^\circ C$		25	50	I	25	50	I	25	50	I	ns	
				60	I		60	I		60	III	ns	
SR Slew Rate	$V_{OUT} = \pm 5V, T_A = 25^\circ C$	$\pm 25$	$\pm 30$		I	$\pm 20$	$\pm 30$		I	$\pm 20$	$\pm 30$	I	V/ $\mu s$
	$V_{OUT} = \pm 5V$	$\pm 20$			I	$\pm 15$			I	$\pm 15$		III	V/ $\mu s$
GBW Gain Bandwidth Products	$A_V \geq 10, T_A = 25^\circ C$		12		V		12		V		12	V	MHz
FPBW Full Power Bandwidth (Note 6)	$V_{OUT} = \pm 10V, T_A = 25^\circ C$	350	500		IV	300	500		IV	300	500	IV	kHz
O.S. Overshoot	$T_A = 25^\circ C$		25	40	I	25	50	I	25	50	I	%	
				50	I		60	I		60	III	%	
$t_s$ Settling Time to 0.1%	$V_{OUT} = \pm 5V, T_A = 25^\circ C$		0.33		V		0.33		V		0.33	V	$\mu s$


- Note 1: Both input currents,  $I_{B+}$  and  $I_{B-}$ , are tested individually.
- Note 2: For CMRR+,  $V_{CM} = 0$  to  $+10V$  and for CMRR-,  $V_{CM} = 0$  to  $-10V$ .
- Note 3: For PSRR+,  $V_S = +10V$  to  $+20V$  with  $V_{S-} = -15V$ .  
For PSRR-,  $V_S = -10V$  to  $-20V$  with  $V_{S+} = +15V$ .
- Note 4: For  $A_{VOL+}$ ,  $V_{OUT} = 0$  to  $+10V$  and for  $A_{VOL-}$ ,  $V_{OUT} = 0$  to  $-10V$ .
- Note 5: Both positive and negative supply currents,  $I_{CC+}$  and  $I_{CC-}$ , are tested.
- Note 6: The Full Power Bandwidth is guaranteed by testing slew rate,  $FPBW = SR / (2\pi V_P)$ .

# EHA2500/2502/2505


## High Slew Rate Operational Amplifier

### Typical Performance Curves


**Input Bias and Offset Current vs Temperature**




**Equivalent Input Noise Voltage vs Frequency**




**Normalized AC Parameters vs Temperature**




**Open-Loop Frequency and Phase Response**




**Normalized AC Parameters vs Supply Voltage at 25°C**




**Open-Loop Frequency Response For Various Compensation**




**Open-Loop Voltage Gain vs Temperature**



**Output Voltage Swing vs Frequency at +25°C**



**Power Supply Current vs Temperature**




# EHA2500/2502/2505

## High Slew Rate Operational Amplifier


EHA2500/EHA2502/EHA2505

### Typical Performance Curves - (continued)


**Voltage Follower Pulse Response**




**8-Lead CerDIP Maximum Power Dissipation vs Ambient Temperature**




**8-Lead Plastic DIP Maximum Power Dissipation vs Ambient Temperature**



**8-Lead TO-99 Metal Can Maximum Power Dissipation vs Ambient Temperature**



**20-Pad LCC Maximum Power Dissipation vs Ambient Temperature**



# EHA2510/2512/2515

## High Slew Rate Operational Amplifier

### Absolute Maximum Ratings

$V_S$	Supply Voltage	$\pm 20V$	$T_A$	Operating Temperature Range:	
$V_{IN}$	Differential Input Voltage	$\pm 15.0V$		EHA2510/12	$-55^\circ C$ to $+125^\circ C$
$P_D$	Maximum Power Dissipation	See Curves		EHA2515	$0^\circ C$ to $+75^\circ C$
$I_{OUT}$	Peak Output Current	50mA	$T_{ST}$	Storage Temperature	$-65^\circ C$ to $+150^\circ C$
				Lead Temperature	
				(soldering, 5 seconds)	300°C

**Important Note:** All parameters having Min./Max. specifications are guaranteed. The Test Level column indicates the specific device testing actually performed during production and Quality Assurance inspection. Elantec performs most electrical tests using modern high-speed automatic test equipment, specifically the ITX 77 Series system. Unless otherwise noted, all tests are pulsed tests, therefore  $T_j = T_c = T_A$ .

### DC Electrical Characteristics

$V_S = \pm 15V$ ,  $R_S = 50\Omega$ ,  $R_L = 100k\Omega$ ,  $V_{CM} = 0V$ ,  $V_{OUT} = 0V$ ,  $T_{MIN} \leq T_A \leq T_{MAX}$ , unless otherwise specified.

Parameter	Test Conditions	EHA2510				EHA2512				EHA2515				Units
		Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	Test Level	
$V_{OS}$	Offset Voltage	$T_A = 25^\circ C$												mV
		4	8	I	5	10	I	5	10	I	5	10	I	
				10	I			14	I			14	III	mV
$\Delta V_{OS}/\Delta T$	Offset Voltage Drift		20		V		25		V		30		V	$\mu V/^\circ C$
$I_B$	Bias Current (Note 1)	$T_A = 25^\circ C$												nA
		100	200	I	125	250	I	125	250	I	125	250	I	
				400	I			500	I			500	III	nA
$I_{OS}$	Offset Current	$T_A = 25^\circ C$												nA
		10	25	I	20	50	I	20	50	I	20	50	I	
				50	I			100	I			100	III	nA
$R_{IN}$	Input Resistance	$T_A = 25^\circ C$	50	100	IV	40	100	IV	40	100	IV	100	IV	M $\Omega$
$V_{CMR}$	Common-Mode Range		$\pm 10.0$		I	$\pm 10.0$		I	$\pm 10.0$		II		V	
$CMRR$	Common-Mode Rejection Ratio (Note 2)	$\Delta V_{CM} = \pm 10V$	80	90	I	74	90	I	74	90	II		dB	
$PSRR$	Power Supply Rejection Ratio (Note 3)	$\Delta V_S = \pm 5V$	80	90	I	74	90	I	74	90	II		dB	
$A_{VOL}$	Large Signal Voltage Gain (Note 4)	$R_L = 2k\Omega$ , $V_{OUT} = \pm 10V$ , $T_A = 25^\circ C$												V/mV
		10	15	I	7.5	15	I	7.5	15	I	7.5	15	I	
		$R_L = 2k\Omega$ , $V_{OUT} = \pm 10V$												V/mV
			7.5		I	5		I	5		III		V/mV	
$V_{OUT}$	Output Voltage Swing	$R_L = 2k\Omega$	$\pm 10.0$	$\pm 12.0$	I	$\pm 10.0$	$\pm 12.0$	I	$\pm 10.0$	$\pm 12.0$	II		V	
$I_{OUT}$	Output Current	$V_{OUT} = \pm 10V$ , $T_A = 25^\circ C$												mA
		$\pm 10$	$\pm 20$	I	$\pm 10$	$\pm 20$	I	$\pm 10$	$\pm 20$	I	$\pm 10$	$\pm 20$	I	
		$V_{OUT} = \pm 10V$												mA
			$\pm 7.5$		I	$\pm 7.5$		I	$\pm 7.5$		III		mA	
$I_{CC}$	Supply Current (Note 5)	$T_A = 25^\circ C$												mA
		4	6	I	4	6	I	4	6	I	4	6	I	
				6.5	I			7	I			7	III	mA



# EHA2510/2512/2515

## High Slew Rate Operational Amplifier

EHA2510/EHA2512/EHA2515

### AC Electrical Characteristics

$V_S = \pm 15V$ ,  $A_V = 1$ ,  $R_S = 50\Omega$ ,  $R_L = 2k\Omega$ ,  $C_L = 50pF$ ,  $V_{OUT} = \pm 200mV$ ,  $T_{MIN} < T_A < T_{MAX}$ , unless otherwise specified (See AC test circuit)

Parameter	Test Conditions	EHA2510				EHA2512				EHA2515				Units
		Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	Test Level	
$t_r, t_f$ Rise and Fall Times	$T_A = 25^\circ C$		25	50	I		25	50	I		25	50	I	ns
				60	I			60	I			60	III	ns
SR Slew Rate	$V_{OUT} = \pm 5V, T_A = 25^\circ C$	$\pm 50$	$\pm 65$		I	$\pm 40$	$\pm 60$		I	$\pm 40$	$\pm 60$		I	V/ $\mu s$
	$V_{OUT} = \pm 5V$	$\pm 45$			I	$\pm 35$			I	$\pm 35$			III	V/ $\mu s$
GBW Gain Bandwidth Products	$A_V \geq 10mV, T_A = 25^\circ C$		12		V		12		V		12		V	MHz
FPBW Full Power Bandwidth (Note 6)	$V_{OUT} = \pm 10V, T_A = 25^\circ C$	750	1000		IV	600	1000		IV	600	1000		IV	kHz
O.S. Overshoot	$T_A = 25^\circ C$		25	40	I		25	50	I		25	50	I	%
				50	I			60	I			60	III	%
$t_s$ Settling Time to 0.1%	$V_{OUT} = \pm 5V$		0.25		V		0.25		V		0.25		V	$\mu s$


- Note 1: Both input currents,  $I_{IH}$ , and  $I_{IL}$ , are tested individually.
- Note 2: For CMRR+,  $V_{CM} = 0$  to +10V and for CMRR-,  $V_{CM} = 0$  to -10V.
- Note 3: For PSRR+,  $V_{S+} = +10V$  to +20V with  $V_{S-} = -15V$ .  
For PSRR-,  $V_{S-} = -10V$  to -20V with  $V_{S+} = +15V$ .
- Note 4: For  $A_{VOL+}$ ,  $V_{OUT} = 0$  to +10V and for  $A_{VOL-}$ ,  $V_{OUT} = 0$  to -10V.
- Note 5: Both positive and negative supply currents,  $I_{CC+}$ , and  $I_{CC-}$ , are tested.
- Note 6: The Full Power Bandwidth is guaranteed by testing slew rate,  $FPBW = SR / (2\pi V_p)$ .

# EHA2510/2512/2515


## High Slew Rate Operational Amplifier

### Typical Performance Curves


**Input Bias and Offset Current vs Temperature**




**Equivalent Input Noise Voltage vs Frequency**




**Normalized AC Parameters vs Temperature**




**Open-Loop Frequency and Phase Response**




**Normalized AC Parameters vs Supply Voltage at 25°C**




**Open-Loop Frequency Response For Various Compensation**




**Open-Loop Voltage Gain vs Temperature**



**Output Voltage Swing vs Frequency at 25°C**



**Power Supply Current vs Temperature**




# EHA2510/2512/2515

## High Slew Rate Operational Amplifier


EHA2510/EHA2512/EHA2515

### Typical Performance Curves


**Voltage Follower Pulse Response**




**8-Lead CerDIP Maximum Power Dissipation vs Ambient Temperature**




**8-Lead Plastic DIP Maximum Power Dissipation vs Ambient Temperature**



**8-Lead TO-99 Metal Can Maximum Power Dissipation vs Ambient Temperature**



**20-Pad LCC Maximum Power Dissipation vs Ambient Temperature**



# EHA2520/2522/2525

## High Slew Rate Operational Amplifier

### Absolute Maximum Ratings

$V_S$	Supply Voltage	$\pm 20V$	$T_A$	Operating Temperature Range:	
$V_{IN}$	Differential Input Voltage	$\pm 15.0V$		EHA2520/22	$-55^\circ C$ to $+125^\circ C$
$P_D$	Maximum Power Dissipation	See Curves		EHA2525	$0^\circ C$ to $+75^\circ C$
$I_{OUT}$	Peak Output Current	50mA	$T_{ST}$	Storage Temperature	$-65^\circ C$ to $+150^\circ C$
				Lead Temperature	
				(soldering, 5 seconds)	300°C

**Important Note:** All parameters having Min./Max. specifications are guaranteed. The Test Level column indicates the specific device testing actually performed during production and Quality Assurance inspection. Elantec performs most electrical tests using modern high-speed automatic test equipment, specifically the LTX 77 Series system. Unless otherwise noted, all tests are pulsed tests, therefore  $T_J = T_C = T_A$ .

### DC Electrical Characteristics

$V_S = \pm 15V$ ,  $R_S = 50\Omega$ ,  $R_L = 100k\Omega$ ,  $V_{CM} = 0V$ ,  $V_{OUT} = 0V$ ,  $T_{MIN} \leq T_A \leq T_{MAX}$ , unless otherwise specified.

Parameter	Test Conditions	EHA2520			EHA2522				EHA2525				Units
		Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	
$V_{OS}$ Offset Voltage	$T_A = 25^\circ C$		4	8	I	5	10	I	5	10	I	mV	
				10	I		14	I		14	III	mV	
$\Delta V_{OS}/\Delta T$ Offset Voltage Drift			20		V	25		V	30		V	$\mu V/^\circ C$	
$I_B$ Bias Current (Note 1)	$T_A = 25^\circ C$		100	200	I	125	250	I	125	250	I	nA	
				400	I		500	I		500	III	nA	
$I_{OS}$ Offset Current	$T_A = 25^\circ C$		10	25	I	20	50	I	20	50	I	nA	
				50	I		100	I		100	III	nA	
$R_{IN}$ Input Resistance	$T_A = 25^\circ C$	50	100		IV	40	100		IV	40	100	IV	M $\Omega$
$V_{CMR}$ Common-Mode Range		$\pm 10.0$			I	$\pm 10.0$			I	$\pm 10.0$		II	V
CMRR Common-Mode Rejection Ratio (Note 2)	$\Delta V_{CM} = \pm 10V$	80	90		I	74	90		I	74	90	II	dB
PSRR Power Supply Rejection Ratio (Note 3)	$\Delta V_S = \pm 5V$	80	90		I	74	90		I	74	90	II	dB
$A_{VOL}$ Large Signal Voltage Gain (Note 4)	$R_L = 2k\Omega$ , $V_{OUT} = \pm 10V$ , $T_A = 25^\circ C$	10	15		I	7.5	7.5		I	7.5	15	I	V/mV
	$R_L = 2k\Omega$ , $V_{OUT} = \pm 10V$	7.5			I	5			I	5		III	V/mV
$V_{OUT}$ Output Voltage Swing	$R_L = 2k\Omega$	$\pm 10.0$	$\pm 12.0$		I	$\pm 10.0$	$\pm 12.0$		I	$\pm 10.0$	$\pm 12.0$	II	V
$I_{OUT}$ Output Current	$V_{OUT} = \pm 10V$ , $T_A = 25^\circ C$	$\pm 10$	$\pm 20$		I	$\pm 10$	$\pm 20$		I	$\pm 10$	$\pm 20$	I	mA
	$V_{OUT} = \pm 10V$	$\pm 7.5$			I	$\pm 7.5$			I	$\pm 7.5$		III	mA
$I_{CC}$ Supply Current (Note 5)	$T_A = 25^\circ C$		4	6	I	4	6	I	4	6	I	mA	
				6.5	I		7	I		7	III	mA	

# EHA2520/2522/2525

## High Slew Rate Operational Amplifier

EHA2520/EHA2522/EHA2525

### AC Electrical Characteristics

$V_S = \pm 15V$ ,  $A_V = 3$ ,  $R_S = 50\Omega$ ,  $R_L = 2k\Omega$ ,  $C_L = 50pF$ ,  $V_{OUT} = \pm 200mV$ ,  $T_{MIN} < T_A < T_{MAX}$  unless otherwise specified (See AC test circuit)

Parameter	Test Conditions	EHA2520				EHA2522				EHA2525				Units
		Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	Test Level	Min.	Typ.	Max.	Test Level	
$t_r, t_f$ Rise and Fall Times	$T_A = 25^\circ C$	25	50	I	25	50	I	25	50	I	25	50	I	ns
		55	I	60	I	60	III	ns						
SR Slew Rate	$V_{OUT} = \pm 5V, T_A = 25^\circ C$	$\pm 100$	$\pm 120$	I	$\pm 80$	$\pm 120$	I	$\pm 80$	$\pm 120$	I	$\pm 120$	III	$V/\mu s$	
	$V_{OUT} = \pm 5V$	$\pm 84$	I	$\pm 60$	I	$\pm 60$	III	$V/\mu s$						
GBW Gain Bandwidth Products	$A_V \geq 10mV, T_A = 25^\circ C$	10	20	IV	10	20	IV	10	20	IV	MHz			
FPBW Full Power Bandwidth (Note 6)	$V_{OUT} = \pm 10V, T_A = 25^\circ C$	1500	2000	IV	1200	1600	IV	1200	1600	IV	kHz			
O.S. Overshoot	$T_A = 25^\circ C$	25	40	I	25	50	I	25	50	I	%			
		45	I	60	I	60	III	%						
$t_s$ Settling Time to 0.1%	$V_{OUT} = \pm 5V, T_A = 25^\circ C$	0.20	V	0.20	V	0.20	V	$\mu s$						


- Note 1: Both input currents,  $I_{B+}$  and  $I_{B-}$ , are tested individually.
- Note 2: For CMRR+,  $V_{CM} = 0$  to  $+10V$  and for CMRR-,  $V_{CM} = 0$  to  $-10V$ .
- Note 3: For PSRR+,  $V_S = +10V$  to  $+20V$  with  $V_S = -15V$ .  
For PSRR-,  $V_S = -10V$  to  $-20V$  with  $V_S = +15V$ .
- Note 4: For  $A_{VOL+}$ ,  $V_{OUT} = 0$  to  $+10V$  and for  $A_{VOL-}$ ,  $V_{OUT} = 0$  to  $-10V$ .
- Note 5: Both positive and negative supply currents,  $I_{S+}$  and  $I_{S-}$ , are tested.
- Note 6: The Full Power Bandwidth is guaranteed by testing slew rate,  $FPBW = SR / (2\pi V_p)$ .

# EHA2520/2522/2525


## High Slew Rate Operational Amplifier

### Typical Performance Curves


**Input Bias and Offset Current vs Temperature**




**Equivalent Input Noise Voltage vs Frequency**




**Normalized AC Parameters vs Temperature**




**Open-Loop Frequency and Phase Response**




**Normalized AC Parameters vs Supply Voltage at 25°C**




**Open-Loop Frequency Response For Various Compensation**




**Open-Loop Voltage Gain vs Temperature**



**Output Voltage Swing vs Frequency at +25°C**



**Power Supply Current vs Temperature**




# EHA2520/2522/2525

## High Slew Rate Operational Amplifier


EHA2520/EHA2522/EHA2525

### Typical Performance Curves - (continued)


**Pulse Response,  $A_v = +3$**




**PSRR vs Frequency**




**8-Lead CerDIP Maximum Power Dissipation vs Ambient Temperature**



**8-Lead Plastic DIP Maximum Power Dissipation vs Ambient Temperature**



**8-Lead TO-99 Metal Can Maximum Power Dissipation vs Ambient Temperature**



**20-Pad LCC Maximum Power Dissipation vs Ambient Temperature**

