

Functional Polymer Capacitors

Solid Electrolytic Capacitors with Functional Polymer

FPCAP

RE Series L1, V1 Type

Low ESR

Low Profile

Lead Free


Features

The Anode is Aluminum foil and the Cathode is a Functional Polymer formed.

- Low ESR at a high frequency range.
- High reliability and high heat range.
- Long life and high reliability.(Reliability:0.1%/1,000Hrs)

Applications

- Switching Power Supply and DC/DC Converter.
- Buck up Power Supplies of CPU(VRM etc.)
- Miniature high Power Supply.



Environmental correspondence


- Any environmental hazardous substances are not used.
- The lead free of terminal plating (Sn 100%)

Specifications

Items		Characteristics	
		Standard type (L1)	Extended capacitance type (V1)
Operating Temp. Range		-55 to +105°C	
Rated Voltage Range		6.3 to 25 V-DC	4.0 to 16 V-DC
Capacitance Range		22 to 330 μF	330 to 820 μF
Capacitance Tolerance		±20% (M)	
Endurance	Condition	105°C 2,000Hrs at rated voltage	
	Capacitance	Within ±20% of the initial value before test	
	Leakage Current	Not to exceed the initial specified value	
	Dissipation Factor	Not to exceed 150% of the initial specified value	
Reliability		0.1% / 1,000Hrs. Max (60%CL)	
Others		JIS-C-5101-4	

Dimensions <Standard type : L1> (φ D×L)

Cap(μF)	R.V.(V)		S.V.(V)						
	4.0	6.3	10	16	20	25	25	25	25
22	4.6								8×10.5
33		7.2							10×10.5
47								8×10.5	10×10.5
68					8×10.5	8×10.5			
100			8×10.5	8×10.5	8×10.5	10×10.5			
150			8×10.5						
220		8×10.5	10×10.5						
330		10×10.5							



<Extended capacitance type : V1> (φ D×L)

Cap(μF)	R.V.(V)		S.V.(V)						
	4.0	6.3	10	16	20	25	25	25	25
330	4.6								10×10.5
390			8×10.5						
470				10×10.5					
560		8×10.5							
680			10×10.5						
820		10×10.5							

(Unit : mm)


φ D×L	φ d	P
8×10.5	0.6	3.5
10×10.5	0.6	5.0

Functional Polymer Capacitors (FPCAP)

● Part number & Specifications

Rated Voltage (V)	Capacitance (μ F)	Part Number	Leakage Current (μ A)	$\tan\delta$	ESR ($m\Omega$, 100kHz)	Maximum permissible Ripple Current (mA, r.m.s.)	Case Size $\phi D \times L$ (mm)
4.0	560	FP-4R0RE561M-V1□□	224.0	0.080	14	4080	8×10.5
	820	FP-4R0RE821M-V1□□	328.0	0.080	12	5040	10×10.5
6.3	150	FP-6R3RE151M-L1□□	18.90	0.070	30	2780	8×10.5
	220	FP-6R3RE221M-L1□□	27.72	0.070	30	3000	8×10.5
	330	FP-6R3RE331M-L1□□	41.58	0.070	25	3500	10×10.5
	390	FP-6R3RE391M-V1□□	245.7	0.080	16	3810	8×10.5
	680	FP-6R3RE681M-V1□□	428.4	0.080	13	4840	10×10.5
10	100	FP-010RE101M-L1□□	20.00	0.070	30	2670	8×10.5
	220	FP-010RE221M-L1□□	44.00	0.070	27	3370	10×10.5
	470	FP-010RE471M-V1□□	470.0	0.080	15	4510	10×10.5
16	68	FP-016RE680M-L1□□	21.76	0.060	36	2700	8×10.5
	100	FP-016RE101M-L1□□	32.00	0.060	30	2740	8×10.5
	150	FP-016RE151M-L1□□	48.00	0.060	28	3260	10×10.5
	330	FP-016RE331M-V1□□	792.0	0.080	17	4580	10×10.5
20	47	FP-020RE470M-L1□□	18.80	0.060	40	2450	8×10.5
	68	FP-020RE680M-L1□□	27.20	0.060	36	2600	8×10.5
	100	FP-020RE101M-L1□□	40.00	0.060	30	3210	10×10.5
25	22	FP-025RE220M-L1□□	11.00	0.060	40	2330	8×10.5
	33	FP-025RE330M-L1□□	16.50	0.060	35	2900	10×10.5
	47	FP-025RE470M-L1□□	23.50	0.060	35	2980	10×10.5

● Part Number (EX) 16V100 μ F



FUJITSU MEDIA DEVICES LIMITED

<http://jp.fujitsu.com/fmd/en/>

Japan Global Sales

Shin-Yokohama Square Bldg., 14F Shin-Yokohama 2-3-12, Kohoku-ku, Yokohama, Kanagawa 222-0033, Japan
Tel: +81-45-471-0061 Fax: +81-45-471-0076

North and South America

FUJITSU MEDIA DEVICES OF AMERICA, INC.
Tel: +1-408-746-7500
Fax: +1-408-746-7555
<http://www.fmda.fujitsu.com/>

Europe

FUJITSU MICROELECTRONICS
EUROPE GmbH
Tel: +49-6103-690-0
Fax: +49-6103-690-122
<http://www.fme.fujitsu.com/>

Asia Pacific

FUJITSU MEDIA DEVICES HONG KONG LTD.
Tel: +852-2866-8509
Fax: +852-2866-8287
(Taiwan Representative office)
Tel: +886-2-2311-2255
Fax: +886-2-2371-8347
FUJITSU MEDIA DEVICES TRADING (SHANGHAI) LTD.
Tel: +86-21-6323-4560
Fax: +86-21-6323-4510

Specifications are subject to change without notice. For further information please contact each office.

The contents of this document are subject to change without notice.

Customers are advised to consult with FUJITSU MEDIA DEVICES sales representatives before ordering.

The information, such as descriptions of function and application circuit examples, in this document are presented solely for the purpose of reference to show examples of operations and uses of FUJITSU MEDIA DEVICES electronic device; FUJITSU MEDIA DEVICES does not warrant proper operation of the device with respect to use based on such information. When you develop equipment incorporating the device based on such information, you must assume any responsibility arising out of such use of the information. FUJITSU MEDIA DEVICES assumes no liability for any damages whatsoever arising out of the use of the information. Any information in this document, including descriptions of function and schematic diagrams, shall not be construed as license of the use or exercise of any intellectual property right, such as patent right or copyright, or any other right of FUJITSU MEDIA DEVICES or any third party or does FUJITSU MEDIA DEVICES warrant non-infringement of any third-party's intellectual property right or other right by using such information. FUJITSU MEDIA DEVICES assumes no liability for any infringement of the intellectual property rights or other rights of third parties which would result from the use of information contained herein. The products described in this document are designed, and manufactured as contemplated for general use, including without limitation, ordinary industrial use, general office use, personal use, and household use, but are not designed, developed and manufactured as contemplated (1) for use accompanying fatal risks or dangers that, unless extremely high safety is secured, could have a serious effect to the public, and could lead directly to death, personal injury, severe physical damage or other loss (i.e., nuclear reaction control in nuclear facility, aircraft flight control, air traffic control, mass transport control, medical life support system, missile launch control in weapon system), or (2) for use requiring extremely high reliability (i.e., submersible repeater and artificial satellite). Please note that FUJITSU MEDIA DEVICES will not be liable against you and/or any third party for any claims or damages arising in connection with above-mentioned uses of the products. Any electronic devices have inherently a certain rate of failure. You must protect against injury, damage or loss from such failures by incorporating safety design measures into your facility and equipment such as redundancy, fire protection, and prevention of over-current levels and other abnormal operating conditions. If any products described in this document represent goods or technologies subject to certain restrictions on export under the Foreign Exchange and Foreign Trade Control Law of Japan, the prior authorization by Japanese government should be required for export of those products from Japan.