

VOLTAGE RANGE: 2500 --- 5000 V
CURRENT: 0.2 A


Features

- ◇ Low cost
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

Mechanical Data

- ◇ Case: JEDEC DO-41, molded plastic
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.012 ounces, 0.33 grams
- ◇ Mounting position: Any

DO-41



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		R2500	R3000	R4000	R5000	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	2500	3000	4000	5000	V
Maximum RMS voltage	V_{RMS}	1750	2100	2800	3500	V
Maximum DC blocking voltage	V_{DC}	2500	3000	4000	5000	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^\circ C$	$I_{F(AV)}$	0.2				A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^\circ C$	I_{FSM}	30.0				A
Maximum instantaneous forward voltage @ 0.2A	V_F	3.0	4.0	5.0		V
Maximum reverse current @ $T_A=25^\circ C$ at rated DC blocking voltage @ $T_A=100^\circ C$	I_R	5.0 50.0				μA
Typical junction capacitance (Note1)	C_J	30				pF
Typical thermal resistance (Note2)	$R_{\theta JA}$	35				$^\circ C/W$
Operating junction temperature range	T_J	- 55 ---- + 150				$^\circ C$
Storage temperature range	T_{STG}	- 55 ---- + 150				$^\circ C$

NOTE: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2. Thermal resistance from junction to ambient.

RATINGS AND CHARACTERISTIC CURVES

FIG.1 – FORWARD DERATING CURVE




FIG.2 – TYPICAL FORWARD CHARACTERISTICS




FIG.3 – PEAK FORWARD SURGE CURRENT




FIG.4 – TYPICAL JUNCTION CAPACITANCE

