

## GSC4418

### N-CHANNEL ENHANCEMENT MODE POWER MOSFET

BVDSS	30V
RDS(ON)	14mΩ
ID	11.5A


### Description

The GSC4418 uses advanced trench technology to provide excellent on-resistance and low gate charge. The SOP-8 package is universally preferred for all commercial-industrial surface mount applications and suited for use as a load switch or in PWM applications.



### Features

- \*Simple Drive Requirement
- \*Lower On-resistance
- \*Fast Switching Characteristic

### Package Dimensions



### Marking :



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	5.80	6.20	M	0.10	0.25
B	4.80	5.00	H	0.35	0.49
C	3.80	4.00	L	1.35	1.75
D	0°	8°	J	0.375 REF.	
E	0.40	0.90	K	45°	
F	0.19	0.25	G	1.27 TYP.	

### Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	$V_{DS}$	30	V
Gate-Source Voltage	$V_{GS}$	±25	V
Continuous Drain Current <sup>3</sup> , $V_{GS}@20V$	$I_D @TA=25^{\circ}C$	11.5	A
Continuous Drain Current <sup>3</sup> , $V_{GS}@20V$	$I_D @TA=70^{\circ}C$	9.7	A
Pulsed Drain Current <sup>1</sup>	$I_{DM}$	40	A
Total Power Dissipation	$P_D @TA=25^{\circ}C$	2.5	W
Linear Derating Factor		0.02	W/°C
Operating Junction and Storage Temperature Range	$T_j, T_{stg}$	-55 ~ +150	°C

### Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance Junction-ambient Max.	$R_{thj-amb}$	50	°C/W

**Electrical Characteristics (T<sub>j</sub> = 25°C unless otherwise specified)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	30	-	-	V	V <sub>GS</sub> =0, I <sub>D</sub> =250uA
Gate Threshold Voltage	V <sub>GS(th)</sub>	1.5	-	3.0	V	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250uA
Forward Transconductance	g <sub>fs</sub>	-	22	-	S	V <sub>DS</sub> =5V, I <sub>D</sub> =10A
Gate-Source Leakage Current	I <sub>GSS</sub>	-	-	±100	nA	V <sub>GS</sub> = ±25V
Drain-Source Leakage Current(T <sub>j</sub> =25°C)	I <sub>DSS</sub>	-	-	1	uA	V <sub>DS</sub> =30V, V <sub>GS</sub> =0
Drain-Source Leakage Current(T <sub>j</sub> =55°C)		-	-	5	uA	V <sub>DS</sub> =24V, V <sub>GS</sub> =0
Static Drain-Source On-Resistance	R <sub>DS(ON)</sub>	-	-	14	mΩ	V <sub>GS</sub> =20V, I <sub>D</sub> =11.5A
		-	-	17		V <sub>GS</sub> =10V, I <sub>D</sub> =10.0A
		-	-	40		V <sub>GS</sub> =4.5V, I <sub>D</sub> =5.0A
Total Gate Charge <sup>2</sup>	Q <sub>g</sub>	-	8.6	-	nC	I <sub>D</sub> =11.5A V <sub>DS</sub> =15V V <sub>GS</sub> =4.5V
Gate-Source Charge	Q <sub>gs</sub>	-	2.5	-		
Gate-Drain ("Miller") Charge	Q <sub>gd</sub>	-	4.9	-		
Turn-on Delay Time <sup>2</sup>	T <sub>d(on)</sub>	-	5.4	-	ns	V <sub>DS</sub> =15V V <sub>GS</sub> =10V R <sub>G</sub> =3Ω R <sub>L</sub> =1.3Ω
Rise Time	T <sub>r</sub>	-	5.1	-		
Turn-off Delay Time	T <sub>d(off)</sub>	-	14.4	-		
Fall Time	T <sub>f</sub>	-	3.7	-		
Input Capacitance	C <sub>iss</sub>	-	758	-	pF	V <sub>GS</sub> =0V V <sub>DS</sub> =15V f=1.0MHz
Output Capacitance	C <sub>oss</sub>	-	180	-		
Reverse Transfer Capacitance	C <sub>rss</sub>	-	128	-		

**Source-Drain Diode**


Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Forward On Voltage <sup>2</sup>	V <sub>SD</sub>	-	-	1.0	V	I <sub>S</sub> =1.0A, V <sub>GS</sub> =0V
Continuous Source Current (Body Diode)	I <sub>S</sub>	-	-	4.3	A	V <sub>D</sub> = V <sub>G</sub> =0V, V <sub>S</sub> =1.0V
Reverse Recovery Time <sup>2</sup>	T <sub>rr</sub>	-	16.9	-	ns	I <sub>S</sub> =11.5A, V <sub>GS</sub> =0V dI/dt=100A/μs
Reverse Recovery Charge	Q <sub>rr</sub>	-	6.6	-	nC	

Notes: 1. Pulse width limited by Max. junction temperature.


2. Pulse width ≤ 300us, duty cycle ≤ 2%.

3. Surface mounted on 1 in<sup>2</sup> copper pad of FR4 board; 125°C/W when mounted on Min. copper pad.


**Characteristics Curve**




**Fig 1. Typical Output Characteristics**




**Fig 2. Transfer Characteristics**




**Fig 3. On-Resistance v.s. Drain Current and Gate Voltage**




**Fig 4. On-Resistance v.s. Junction Temperature**




**Fig 5. On-Resistance v.s. Gate-Source Voltage**




**Fig 6. Body Diode Characteristics**




**Fig 7. Maximum Safe Operating Area**




**Fig 8. Single Pulse Maximum Power Dissipation**



**Fig 9. Gate Charge Characteristics**



**Fig 10. Typical Capacitance Characteristics**



**Fig 11. Normalized Maximum Transient Thermal Impedance**

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

**Head Office And Factory:**

- Taiwan: No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- China: (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165