

## FSP084-DMAA1 (Efficiency Level V, RoHS Compliant) 84 Watts Power Adapter



- · High efficiency and reliability
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- Complies with FCC part 15, and CISPR 22 class B
- Approved by CUL/UL60950-1  $\,^{2nd}$  TUV EN60950-1  $\,^{2nd}$  , CB 60950-1  $\,^{2nd}$  , FCC, EMC

## **Specification**

- Temperature Range: Operating:  $0^{\circ}$ C ~ +40°C
- Humidity: 80% on operating, 80% on storage
- Average Efficiency: Efficiency Level V & ErP Teir 2
- No Load Power Consumption: Less than 0.5W
- **Dimensions** (LxWxH): 160x58.0x32.3mm

/6.3x2.28x1.26inch

## **Output Characteristics**

SPI Model	Output Voltage	Output Current	Connecter Type	Connecter IDxODxL	Dc cable Length (mm)
AD084DMAA1-J25	12V	7A	Barrel 180°	2.5x5.5x12	1200

Sparkle Power Inc. Main Office 1000 Rock Avenue San Jose, CA 95131

TEL: 408-519-8888 FAX: 408-519-9999

E-MAIL: info@sparklepower.com

Sparkle Power Inc. Los Angeles Office 17071 Green Drive

City of Industry, CA 91745 TEL: 626-839-7180

FAX: 626-839-3395