

This document was generated on 04/04/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>10-18-1035</u>

Status: Active
Overview: Standard .093"

Description: 2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 2 Male

Terminals, 1 Female Terminal

Documents:

3D Model RoHS Certificate of Compliance (PDF)

Drawing (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series 3099

Application Power, Wire-to-Board Comments Solder Type|Round Pin

Overview Standard .093"
Product Name Standard .093"

Physical

Breakaway No Circuits (Loaded) 3 Circuits (maximum) 3 Color - Resin Black Durability (mating cycles max) 25 Flammability 94V-2 **Glow-Wire Compliant** No Lock to Mating Part Yes

Material - Metal Phosphor Bronze

Material - Plating Mating
Tin
Material - Plating Termination
Tin
Material - Resin
Polyester
Number of Rows
1
Orientation
Vertical
PC Tail Length
PCB Locator
PCB Retention
None


PCB Retention PCB Thickness - Recommended 1.60mm Packaging Type Bag Pitch - Mating Interface 5.03mm Plating min - Mating 1.270µm Plating min - Termination 1.270µm Polarized to PCB Yes Shrouded Fully Stackable No Surface Mount Compatible (SMC) No

Temperature Range - Operating -40°C to +105°C Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 5A Voltage - Maximum 250V

Material Info



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Not Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

3099 Series

Mates With

03091081, 03091032

Reference - Drawing Numbers Sales Drawing

SDA-3099-*3**

This document was generated on 04/04/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION