



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
3. PHOSPHOR BRONZE PER QQ-B-750
4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
5. TEFLON MIL-P-19468
6. JIS H 3260, C 3501

1. CRIMPED FERRULE  
HEX CRIMP SIZE .178"
2. CRIMPED CONTACT PIN  
HEX CRIMP SIZE .068"

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO	SCALE	2.5/1	ISSUE	A	FILE NO
7	FERRULE	NOTE 6	NOTE 2	1	FR-52/44-38/3X14	DIMENSIONS ARE IN MILLIMETERS				PART NO. B632100-001-NT3G-5-50
6	SPACER	NOTE 1	NOTE 2	1	SP-35F/17X113	UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED DATE 10-11-01'
5	SLEEVE	DELTRIN	NATURAL	1	SL-25/17X6	0.5-6 = ±0.2				CHECKED DATE 10-11-01'
4	CONTACT PIN	NOTE 3	NOTE 4	1	B74000-8-25/06	6-30 = ±0.4				DRAWN DATE 10-11-01'
3	LOCK RING	NOTE 1	NOTE 2	1	B5071A1-4	30-120 = ±0.6				
2	INSULATOR	NOTE 5	NATURAL	1	112636-2T-50	120-315 = ±1				
1	BODY	NOTE 1	NOTE 2	1	112636-1-38/27	315-1000 = ±1.6				
						1000-2000 = ±2.4				

# Amphenol

TITLE BNC BULKHEAD JACK  
(FOR RG-174/U, 188A/U, 316/U)

DRAWING NO. KJ-B632100-001-NT3G-316U-50

ITEM NO.