

EXAMPLE & ORDERING CODE

RCA - 011 W -

BODY STYLE:
SEE CATALOG PAGES 191-193

COLOR:

BLACK	=	B
RED	=	R
WHITE	=	W
YELLOW	=	Y
WHITE/RED <small>(TOP/BOTTOM)</small>	=	WR

PLATING:

NICKEL, SILVER	=	BLANK
GOLD FLASH	=	G

SPECIFICATIONS

MATERIAL AND FINISH:

Housing:
Material: ABS
Rating: UL 94-HB

Contacts:
Earth Terminal:
Material: SPCC
Plating: Nickel, Silver
Tip Terminal:
Material: Brass
Plating: Nickel, Silver
Shunt Terminal:
Material: Brass
Plating: Nickel, Silver

MECHANICAL SPECIFICATIONS:

Insertion Force: 3 kg max.
Extraction Force: 0.8 to 3 kg

ELECTRICAL SPECIFICATIONS:

Insulator Resistance: 100 Megaohm min. @ 500 VDC
Dielectric Withstanding Strength: 500 VAC @ 50/60 Hz for 1 minute
Contact Resistance: 30 milliohm max. @ 1 kHz and less than 100 milliamps
Soldering Heat: 270°C ± 5°C for 5 ± 0.5 seconds
Current Rating: 1A