


# L 253 100 11 P.C.B. connectors

► Expert Range



Male socket.  
Vertical closed sockets.




Plug  
**RECTANGULAR SHAPE**

Pin 0.8 x 0.8 x 3.4 mm  
.031" x .031" x .134"

P.C.B. thickness ≤ 2.4 mm .094"  
P.C.B. holes Ø 1.3 mm .051"

Body : UL94 V0 - PA  
Grey □

## Spacing 3.81 mm .150"



Socket L 253 100 11  
compatible with :




L 243 200 01



### Ordering details

N. Poles	Weight kg	Packaging	L. mm	Order code
2	0.0004	100	9.01	1SSA <b>253 102</b> R1100
3	0.0006	100	12.82	1SSA <b>253 103</b> R1100
4	0.0008	100	16.63	1SSA <b>253 104</b> R1100
5	0.0010	100	20.44	1SSA <b>253 105</b> R1100
6	0.0012	50	24.25	1SSA <b>253 106</b> R1100

Other numbers of poles, consult us



### Technical data


	IEC	UL / CSA
Wire size		
Screw		
Solid wire		
Stranded wire		
With ferrule		
Rated voltage	160 V	300 V
Rated current	10 A	10 A
Short-circuit current		
Rated wire size / Gauge		
Storage temperature range	-20 ~ +80 °C	
Insulation resistance	≥ 10 <sup>9</sup> Ω	
Wire stripping length		
Recommended screwdriver		
Recommended torque		
Protection		

### Accessories


Rep.	Description	Type	Order code	Packaging	Weight kg
1	Coding peg		1SSA <b>299 084</b> R0600	50	0.0005

### Other versions, please consult us :

Vertical closed sockets with flanges and inserts.



**L 253 100 31**



Socket L 253 100 31  
compatible with :



L 243 200 31