# BGA Heat Sink (High Aspect Ratio Ext.) **Straight Fin**





ATS Part#:

Description:

#### ATS010010005-SF-1D

10.00 x 10.00 x 5.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin

Heat Sink Type: Straight Fin Heat Sink Attachment: Equivalent Part Number: N/A

superGRIP

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- · High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Features a low profile, slant fin array that offers many of the performance benefits of maxiFLOW™ at a great value .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

### **Thermal Performance**

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 58.23 °C/W          | 51.9 °C/W           | 47.3 °C/W           | 43.7 °C/W           | 40.8 °C/W           | 38.5 °C/W           | 36.4 °C/W           |
|                    | Ducted Flow   | 42.8                | 35.9                | 31.6                | 28.6                | 26.4                | 24.6                | 23.2                |

## **Product Detail**

| Schematic Image                               | Dimension A   | Dimension B  | Dimension C  | Dimension D   | тім                | Finish         |
|---|---|--|--|---|--------------------|----------------|
| Mar   | 10.00 mm  | 10.00 mm   | 5.00 mm  | 10 mm   | N/A                | BLACK-ANODIZED |
| Image above is for illustration purpose only. | <ul> <li>Dimension</li> <li>Dimension</li> <li>Thermal papplication</li> <li>ATS resension</li> <li>ATS resension</li> <li>ATS certifier</li> </ul> | n <b>D</b> is fin tip to fin tip<br>performance data are<br>n.<br>rves the right to upda<br>nce. | e provided for refere<br>ate or change its pro<br>k assembly is RoHS | m of the base to the<br>nce only. Actual per<br>ducts without notice<br>6-6 and REACH com<br>ble. | formanc<br>to impr | e may vary by  |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA