

Part Number: C9206A

Revision Date: 2/15/2013

15C 24 AWG 7/32 TC PVC / OAS / Braid / PVC



A. CONSTRUCTION

Conductor: #24 AWG 7/32 Tinned Copper
 Insulation: .010" Polyvinyl Chloride (PVC)
 Cable Core: Cable 15/C @ 2.75" LHL w/ clear polyester wrap
 Shield: 24AWG 7/32 TC Drain wire, Aluminum / Polyester / Aluminum 100% coverage
 Braid: 70% Tinned Copper Braid
 Jacket: .032" Polyvinyl Chloride (PVC) jacket
 Ripcord under Jacket"
CAROL® EXZEL™ -- C9206A -- 15C 24 AWG SHIELDED E105765-H (UL) TYPE CM 105C OR AWM 2464 80C 300V VW-1 --- LL69381 CSA TYPE CMG 105C FT4 -- CE -- -- ROHS -- MADE IN USA (DATE CODE) (TRUMARK SEQUENTIAL FOOTAGE)

DIAMETERS

.023" Nom
 .043" Nom
 .206" Nom
 .292" Nom

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	CM/CMG: 105C, AWM: 80C
Suggested Working Voltage:	300V
Conductor DCR:	26.97 Ohms/M' @ 20°C (Nom)
Mutual Capacitance:	29.8 pF/ft. @ 1 kHz (Nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	BROWN
3	RED
4	ORANGE
5	YELLOW
6	GREEN
7	BLUE
8	PURPLE
9	GRAY
10	WHITE

COLOR CODE

ITEM	COLOR
11	WHITE with BLACK stripe
12	WHITE with BROWN stripe
13	WHITE with RED stripe
14	WHITE with ORANGE stripe
15	WHITE with YELLOW stripe

E. CUSTOMER APPROVAL

Signature: _____
 Date: _____