


## Armoire de table ou pour montage sur bâti

### Caractéristiques :



- Construction en acier de calibre 16.
- Choix de trois profondeurs :
  - 13 po (330 mm)
  - 17,5 po (444 mm)
  - 24,5 po (622 mm)
- Deux (2) paires de rails fixes à trous ronds poinçonnés conformes à la norme EIA-310-D pour montage sur bâti de 19 po.
- Comprend des pattes en caoutchouc, des poignées de levage, une trousse de départ d'écrous clipsables et de vis noires assorties 1421ABK.
- Offerte avec revêtement en poudre texturé noir ou gris clair (RAL7035).
- Capacité de charge recommandée de 600 lb.
- Conforme à la directive RoHS.
- Fabriqué en Amérique du Nord.

### Accessoires

Part No.	Part No.	Overall Dimensions			Usable Mounting Dimensions		Rack Units Included	Number of Clip Nuts	S
					Height	Depth			
Black	Light Gray	Height	Width	Depth	Height	Depth	Units	Included	
RCBS1900313BK1	RCBS1900313LG1	5.50	21.00	13.00	3.50	12.38	2U	8	
RCBS1900513BK1	RCBS1900513LG1	7.25	21.00	13.00	5.25	12.38	3U	8	
RCBS1900713BK1	RCBS1900713LG1	9.00	21.00	13.00	7.00	12.38	4U	8	
RCBS1900813BK1	RCBS1900813LG1	10.75	21.00	13.00	8.75	12.38	5U	16	
RCBS1901013BK1	RCBS1901013LG1	12.50	21.00	13.00	10.50	12.38	6U	16	
RCBS1901213BK1	RCBS1901213LG1	14.25	21.00	13.00	12.25	12.38	7U	16	
RCBS1901413BK1	RCBS1901413LG1	16.00	21.00	13.00	14.00	12.38	8U	16	
RCBS1900317BK1	RCBS1900317LG1	5.50	21.00	17.50	3.50	16.88	2U	8	
RCBS1900517BK1	RCBS1900517LG1	7.25	21.00	17.50	5.25	16.88	3U	8	
RCBS1900717BK1	RCBS1900717LG1	9.00	21.00	17.50	7.00	16.88	4U	8	
RCBS1900817BK1	RCBS1900817LG1	10.75	21.00	17.50	8.75	16.88	5U	16	
RCBS1901017BK1	RCBS1901017LG1	12.50	21.00	17.50	10.50	16.88	6U	16	
RCBS1901217BK1	RCBS1901217LG1	14.25	21.00	17.50	12.25	16.88	7U	16	
RCBS1901417BK1	RCBS1901417LG1	16.00	21.00	17.50	14.00	16.88	8U	16	
RCBS1900324BK1	RCBS1900324LG1	5.50	21.00	24.50	3.50	23.88	2U	8	
RCBS1900524BK1	RCBS1900524LG1	7.25	21.00	24.50	5.25	23.88	3U	8	
RCBS1900724BK1	RCBS1900724LG1	9.00	21.00	24.50	7.00	23.88	4U	8	
RCBS1900824BK1	RCBS1900824LG1	10.75	21.00	24.50	8.75	23.88	5U	16	
RCBS1901024BK1	RCBS1901024LG1	12.50	21.00	24.50	10.50	23.88	6U	16	
RCBS1901224BK1	RCBS1901224LG1	14.25	21.00	24.50	12.25	23.88	7U	16	

*Les données sont sujettes à changement sans préavis.*

© 2014. Hammond Manufacturing Ltd. Tous droits réservés.