



SWITCH CHARACTERISTICS

OPERATING POSITION----- 782 TO 842
 PRETRAVEL----- 050 MAX
 OVERTRAVEL----- 218 MIN
 MOVEMENT DIFFERENTIAL----- 015 MAX
 OPERATING FORCE-----425 MAX

OPERATING CHARACTERISTICS
 TAKEN AT BUTTON.
 COM. AND N.O. TERMINALS ARE
 250 X .032

ELECTRICAL RATING

0.1 AMP 125 VAC

U.L. RECOGNIZED
 AND
 CSA CERTIFIED

DWG: TLM		THE CONFIDENTIAL AND PROPRIETARY INFORMATION CONTAINED IN THIS DOCUMENT IS OWNED BY CHERRY ELECTRICAL PRODUCTS. A DIVISION OF THE CHERRY CORPORATION WHO MUST GIVE WRITTEN PERMISSION BEFORE THE DOCUMENT OR INFORMATION CAN BE COPIED.		3600 SUNSET AVENUE WAUWATON, WI 53090	
APVD: N R		DATE: 14-Dec-01		ELECTRICAL PRODUCTS	
DATE: 14-Dec-01		THIS SINGLE PROJECTION		TOLERANCE UNLESS SPECIFIED	
REV: A		ECN NO: 96238		DATE: 14-Dec-01	
DATE: 14-Dec-01		PREP: TLM		APVD: N R	
PROJECT: FG1-1157 A		ITEM NO: OG1301M0 SPEC DRWG		SCALE: SH 1 OF 1	

ORIGINAL OR PROVE