### C1005NP01H080D050BA



#### TDK item description C1005NP01H080DT\*\*\*\*

Applications	Commercial Grade Please refer to Part No. <u>CGA2B2NP01H080D050BA</u> for Automotive use.	
Feature	150°C High Temperature Application	
Series	C1005 [EIA 0402]	Le G
Status	Production	Dimension

Size	
Length(L)	1.00mm ±0.05mm
Width(W)	0.50mm ±0.05mm
Thickness(T)	0.50mm ±0.05mm
Terminal Width(B)	0.10mm Min.
Terminal Spacing(G)	0.30mm Min.
Recommended Land Pattern (PA)	0.30mm to 0.50mm
Recommended Land Pattern (PB)	0.35mm to 0.45mm
Recommended Land Pattern (PC)	0.40mm to 0.60mm

Electrical Characteristics		
Capacitance	8pF ±0.5pF	
Rated Voltage	50VDC	
Temperature Characteristic	NP0(0±30ppm/°C)	
Q (Min.)	560	
Insulation Resistance (Min.)	10000ΜΩ	


Other	
Soldering Method	Reflow
AEC-Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	10000pcs

! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.


! All specifications are subject to change without notice.

### C1005NP01H080D050BA







## Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



### C1005NP01H080D050BA





#### **Temperature Characteristic** 8.02p Capacitance(Nom.)/F 8.015p 8.01p 8.005p 8p 7.995p 0 rdo G Ф 2 Ъ ra る 10 re, °Co °D Temperature/degC C1005NP01H080D050BA(DC Bias = 25V) C1005NP01H080D050BA(No Bias)

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.


! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.

### C1005NP01H080D050BA



# Associated Images



! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.