



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. RATING: 20VDC @ 1mA or 5VDC @ 5mA
  4. CONTACT RESISTANCE: 200Ω MAX. @ 5VDC, 1mA
  5. INSULATION RESISTANCE: 100MΩ MIN. @ 100VDC.
  - ▲ 6. OPERATING FORCE: 125± 35gf
  7. TRAVEL: 1.3 +/-0.3 mm
  8. OPERATING TEMPERATURE: -20°C TO 70°C
  9. OPERATING LIFE: 300,000 CYCLES
  - ▲ 10. LED: BLUE
  11. ▲ DENOTES CRITICAL PARAMETERS
  12. 2002/95/EC (ROHS) COMPLIANT

▲ LED SPECS	UNITS	BLUE
FORWARD CURRENT	mA	20 NOMINAL
FORWARD VOLTAGE @20mA	V	3.50 TYP. 4.00 MAX.
LUMINOUS INTENSITY @ 20mA	mcd	1500 TYP.



TITLE LP2S2WHTBLU-N

A	18647	NEW RELEASE	9-14-09	RC
REV	PCR NO	DESCRIPTION	DATE	BY

SCALE	DATE	DR	DWG	REV
2=1	8/25/2009	RC	B250005	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED