

Electronic housing - HCS-T MICRO X 2AA C C 7035 - 2203127

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Handheld housing, T-Micro, light gray, consisting of two half shells, screws, front 1.1 mm recessed, closed with keypad slot, battery compartment cover and battery contacts, for 2 AA batteries

Why buy this product

- ✓ Suitable for handheld devices

- ☑ Degree of protection: up to IP54
- ▼ Temperature range: -20 °C to +50 °C
- ✓ Flammability rating UL 94-V0



Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 376851
GTIN	4055626376851

Technical data

Item properties

Туре	HCS-T MICRO X 2AA C C 7035
Order No.	2203127
Туре	straight
Max. IP code to attain	IP40
Housing type	Complete housing
Battery compartment	2 x AA

Measurements



Electronic housing - HCS-T MICRO X 2AA C C 7035 - 2203127

Technical data

Measurements

Caption	Schematic representation – for additional information, see product range drawing in the Download Center
Width [w]	48 mm
Height [h]	150 mm
Depth [d]	28 mm

Material specifications

Housing material	ABS
Color (RAL)	light gray (7035)

Standards and Regulations

Flammability rating according to UL 94	V0

Drawings

Dimensional drawing



Schematic representation – for additional information, see product range drawing in the Download Center

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com