Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

9985 Hook-up/Lead - UL AWM Style 1061



For more Information please call

1-800-Belden1



General Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

| Physical Characteristics (Overall) | |
|--|-----------------|
| Conductor AWG: | |
| # Conductors AWG Stranding Conductor Material | |
| 1 26 7x34 TC - Tinned Copper | |
| Total Number of Conductors: | 1 |
| Insulation | |
| Insulation Material: | |
| Insulation Material Wall Thickness (mm) PVC - Polyvinyl Chloride 0.254 | |
| Overall Insulation | |
| Overall Cable | |
| Overall Nominal Diameter: | 0.991 mm |
| Mechanical Characteristics (Overall) | |
| Bulk Cable Weight: | 2.232 Kg/Km |
| Applicable Specifications and Agency Compliance (| (Nerell) |
| Applicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs | Overally |
| UL Rating: | 300 V RMS, 80°C |
| UL Type: | AWM 1061 |
| CSA Rating: | 300 V RMS, 80°C |
| CSA Type: | AWM I, A/B |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 10/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Flame Test | |
| UL Flame Test: | VW-1 |
| CSA Flame Test: | FT1 |
| Plenum/Non-Plenum | |
| Fieldin/NOII-Fieldin | |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------------|----------|-------------|--------|-------|----------------|
| 9985 001100 | 100 FT | 0.200 LB | BROWN | | 26 STR PVC BRN |
| 9985 0011000 | 1,000 FT | 2.000 LB | BROWN | P | 26 STR PVC BRN |
| 9985 002100 | 100 FT | 0.200 LB | RED | | 26 STR PVC RED |
| 9985 0021000 | 1,000 FT | 2.000 LB | RED | P | 26 STR PVC RED |
| 9985 003100 | 100 FT | 0.200 LB | ORANGE | | 26 STR PVC ORG |

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

9985 Hook-up/Lead - UL AWM Style 1061

| 9985 0031000 | 1,000 FT | 2.000 LB | ORANGE | P | 26 STR PVC ORG | |
|--------------|----------|----------|-------------|---|-------------------|--|
| 9985 004100 | 100 FT | 0.200 LB | YELLOW | | 26 STR PVC YEL | |
| 9985 0041000 | 1,000 FT | 2.000 LB | YELLOW | P | 26 STR PVC YEL | |
| 9985 005100 | 100 FT | 0.200 LB | GREEN, DARK | | 26 STR PVC GRN | |
| 9985 0051000 | 1,000 FT | 2.000 LB | GREEN, DARK | P | 26 STR PVC GRN | |
| 9985 008100 | 100 FT | 0.200 LB | GRAY | | 26 STR PVC GRY | |
| 9985 0081000 | 1,000 FT | 2.000 LB | GRAY | P | 26 STR PVC GRY | |
| 9985 009100 | 100 FT | 0.200 LB | WHITE | | 26 STR PVC WHT | |
| 9985 0091000 | 1,000 FT | 2.000 LB | WHITE | P | 26 STR PVC WHT | |
| 9985 010100 | 100 FT | 0.200 LB | BLACK | | 26 STR PVC BLK | |
| 9985 0101000 | 1,000 FT | 2.000 LB | BLACK | P | 26 STR PVC BLK | |
| 9985 013100 | 100 FT | 0.200 LB | BLUE, DARK | | 26 STR PVC DK.BLU | |
| 9985 0131000 | 1,000 FT | 2.000 LB | BLUE, DARK | P | 26 STR PVC DK.BLU | |

Notes:

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 1 Revision Date: 08-16-2013

© 2015 Belden, Inc All Rights Reserved

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU ROHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and belief at the date of its publication. The information provided to this best duct Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden belares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.