

Surface Mount Type

POSCAP

Series : TC



Features

- Guaranteed at 125 °C
- RoHS compliance, Halogen free

Specifications

Size code	D2E	D3L	D4
Category temperature range	-55 °C to +125 °C		
Rated voltage range	4 V.DC to 6.3 V.DC	2.5 V.DC to 10 V.DC	
Category voltage range	3.2 V.DC to 5.0 V.DC	2.0 V.DC to 8.0 V.DC	
Rated capacitance range	100 µF to 330 µF	150 µF to 680 µF	330 µF to 1000 µF
Capacitance tolerance	±20 % (120 Hz / + 20 °C)		
Leakage current	Please see the attached characteristics list		
Dissipation factor (tan δ)	Please see the attached characteristics list		
Surge voltage (V.DC)	Rated voltage × 1.15		
Endurance	+125 °C, 1000 h Category temperature range voltage applied		
	Capacitance change	Within ±20 % of the initial value	
	tan δ	≤ 2 times of the initial limit	
	DC leakage current	≤ 2 times of the initial limit	
Damp heat (Steady State)	+60 °C, 90 % to 95 %, 500 h, No-applied voltage		
	Capacitance change	Within +50 %, -20 % of the initial value (ETCF1000M6H (5H))	
	tan δ	≤ 1.5 times of the initial limit	
	DC leakage current	≤ 3 times of the initial limit	

Marking

R. Voltage (VDC)	2.5	4.0	6.3	10.0
Code	e	g	j	A

Dimensions (not to scale)

Unit : mm

Size code	L±0.3	W±0.2	H±0.2*1	S±0.2	W1±0.1
D2E	7.3	4.3	1.8	1.3	2.4
D3L	7.3	4.3	2.8	1.3	2.4
D4	7.3	4.3	3.8	1.3	2.4

* Externals of figure are the reference.
* 1 ±0.1 : D2E

Characteristics list

Series	Rated voltage (V.DC)	Rated temp. (°C)	Category voltage (V.DC)	Category temp. (°C)	Rated capacitance (μF)	Case size (mm)			Size code	Specifications				Standard		Floor life	
						L	W	H		Ripple* ¹ current (mA r.m.s.)	ESR* ² (mΩ max.)	tan δ* ³	LC* ⁴ (μA)	Part number	Min. Packaging Qty (pcs)	Reflow Temp ≤ 260°C	Reflow Temp ≤ 250°C
TCE	2.5	105	2.0	125	680	7.3	4.3	2.8	D3L	3500	12	0.10	170.0	ETCE680MCL	2500	3	2a
		105	2.0	125		7.3	4.3	2.8		3100	15	0.10	170.0	ETCE680MFL	2500		
		105	2.0	125	1000	7.3	4.3	3.8	D4	3900	15	0.15	250.0	ETCE1000MF	2000		
	4	105	3.2	125	150	7.3	4.3	1.8	D2E	2800	18	0.10	60.0	4TCE150MI	3000		
										3100	15	0.10	88.0	4TCE220MF	3000		
		220	2800	18	0.10	88.0	4TCE220MI	3000									
			2400	25	0.10	88.0	4TCE220M	3000									
		330	2800	18	0.10	132.0	4TCE330MI	3000									
			2400	25	0.10	132.0	4TCE330M	3000									
		470	105	3.2	125	7.3	4.3	2.8	D3L	3500	12	0.10	188.0	4TCE470MCL	2500		
										3100	15	0.10	188.0	4TCE470MFL	2500		
			2800	18	0.10	188.0	4TCE470MIL	2500									
										2400	25	0.10	188.0	4TCE470ML	2500		
	6.3	105	5.0	125	100	7.3	4.3	1.8	D2E	2800	18	0.10	63.0	6TCE100MI	3000		
										2400	25	0.10	63.0	6TCE100M	3000		
		150	3100	15	0.10	94.5	6TCE150MF	3000									
			2800	18	0.10	94.5	6TCE150MI	3000									
		220	2400	25	0.15	94.5	6TCE150M	3000									
			2800	18	0.15	138.6	6TCE220MI	3000									
		330	105	5.0	125	7.3	4.3	1.8	D3L	2400	25	0.15	138.6	6TCE220M	3000		
										3100	15	0.10	207.9	6TCE330MFL	2500		
			2800	18	0.10	207.9	6TCE330MIL	2500									
										2400	25	0.10	207.9	6TCE330ML	2500		
	470	105	5.0	125	7.3	4.3	3.8	D4	3500	18	0.15	296.1	6TCE470MI	2000			
									3000	25	0.15	296.1	6TCE470M	2000			
		680	3500	18	0.15	428.4	6TCE680MI		2000								
			3000	25	0.15	428.4	6TCE680M		2000								
		105	8.0	125	220	7.3	4.3		2.8	D3L	2800	18	0.10	220.0	10TCE220MIL		
2400											25	0.10	220.0	10TCE220ML	2500		
105	8.0	125	330	7.3	4.3	3.8	D4	3000	25	0.10	330.0	10TCE330M	2000				
TCF	2.5	105	2.0	125	680	7.3	4.3	2.8	D3L	4400	6	0.10	170.0	ETCF680M6L	2500	3	
										4400	7	0.10	170.0	ETCF680M7L	2500		
										4400	10	0.10	170.0	ETCF680ML	2500		
		1000	7.3	4.3	3.8	D4	6100	5	0.10	170.0	ETCF680M5H	2000					
							6100	5	0.10	250.0	ETCF1000M5H	2000					
							5600	6	0.10	250.0	ETCF1000M6H	2000					
	4	105	3.2	125	330	7.3	4.3	2.8	D3L	4000	12	0.10	132.0	4TCF330ML	2500		
										4400	10	0.10	188.0	4TCF470ML	2500		
	6.3	105	3.2	125	680	7.3	4.3	3.8	D4	4400	10	0.10	272.0	4TCF680MAH	2000		
										220	105	5.0	125	7.3	4.3		
		4600	9	0.10	138.6	6TCF220M9L	2500										
		330	4000	12	0.10	138.6	6TCF220ML	2500									
									470		7.3	4.3	3.8	D4	3900		
		4400	10	0.10	296.1	6TCF470MAH	2000										
105	10.0	125	150	7.3	4.3	2.8	D3L	3600	15	0.10	150.0	10TCF150ML	2500				

*1 Ripple current (100 kHz/ +45 °C), *2 ESR (100 kHz/+20 °C) *3 tan δ (120 Hz/+20 °C) *4 After 5 minutes

◆ Please refer to each page in this catalog for "Reflow conditions" and "Taping specifications".

Guidelines and precautions regarding the technical information and use of our products described in this online catalog.

- If you want to use our products described in this online catalog for applications requiring special qualities or reliability, or for applications where the failure or malfunction of the products may directly jeopardize human life or potentially cause personal injury (e.g. aircraft and aerospace equipment, traffic and transportation equipment, combustion equipment, medical equipment, accident prevention, anti-crime equipment, and/or safety equipment), it is necessary to verify whether the specifications of our products fit to such applications. Please ensure that you will ask and check with our inquiry desk as to whether the specifications of our products fit to such applications use before you use our products.
- The quality and performance of our products as described in this online catalog only apply to our products when used in isolation. Therefore, please ensure you evaluate and verify our products under the specific circumstances in which our products are assembled in your own products and in which our products will actually be used.
- If you use our products in equipment that requires a high degree of reliability, regardless of the application, it is recommended that you set up protection circuits and redundancy circuits in order to ensure safety of your equipment.
- The products and product specifications described in this online catalog are subject to change for improvement without prior notice. Therefore, please be sure to request and confirm the latest product specifications which explain the specifications of our products in detail, before you finalize the design of your applications, purchase, or use our products.
- The technical information in this online catalog provides examples of our products' typical operations and application circuits. We do not guarantee the non-infringement of third party's intellectual property rights and we do not grant any license, right, or interest in our intellectual property.
- If any of our products, product specifications and/or technical information in this online catalog is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially with regard to security and export control, shall be observed.

<Regarding the Certificate of Compliance with the EU RoHS Directive/REACH Regulations>

- The switchover date for compliance with the RoHS Directive/REACH Regulations varies depending on the part number or series of our products.
- When you use the inventory of our products for which it is unclear whether those products are compliant with the RoHS Directive/REACH Regulation, please select "Sales Inquiry" in the website inquiry form and contact us.

We do not take any responsibility for the use of our products outside the scope of the specifications, descriptions, guidelines and precautions described in this online catalog.
